

Zyxel GS1100-16 Unmanaged Gigabit Ethernet (10/100/1000)

Gamintojas: **ZYXEL** · Modelis: **GS1100-16-EU0103F** · EAN: **4718937614066** · Prekės kodas: **652340**



113,90 €

Kaina su PVM

Be PVM: **94,13 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ IEEE 802.3 10BASE-T Ethernet
- ✓ IEEE 802.3u 100BASE-TX Ethernet
- ✓ IEEE 802.3ab 1000BASE-T Ethernet
- ✓ IEEE 802.3az EEE support
- ✓ IEEE 802.3x flow control
- ✓ IEEE 802.3z 1000BASE-X
- ✓ IEEE 802.1p CoS



Aprašymas

Plug and play connectivity

Simply unbox the GS1100 unmanaged switch, you can enjoy instant plug-n-play Gigabit connectivity without any additional settings required with auto-negotiation and auto MDI/MDI-X. Supporting 802.1p prioritization and jumbo frame, the switch ensures smooth voice and video traffic for your office network.

Whisper quiet operation

The GS1100 Series has fanless design that ensures silent operation in small or quiet office environments. The GS1100-10HP PoE model is specifically designed with an external power adapter that eliminates the need for an additional fan to cool down the device, making it perfect for quiet PoE deployments.

Energy saving

The GS1100 features Energy Efficient Ethernet(IEEE 802.3az) which automatically detects network traffic and adjusts power consumption dynamically. Zyxel's green features also adjust power consumption by detecting the link status and cable length reducing business operating expenses.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Network	
Networking standards	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6
Flow control support	Yes
Auto MDI/MDI-X	Yes
Active link detection	Yes
Data transmission	
MAC address table	8000 entries
Switching capacity	32 Gbit/s
Forwarding rate	23.8 Mpps
Jumbo frames support	Yes
Jumbo frames	9216
Packet buffer memory	0.5 MB
Design	
Rack mounting	Yes
LED indicators	Activity, Link, Power
Wall mountable	Yes
Electromagnetic compatibility	CE, FCC, RCM, ICES-003, BSMI
Performance	
Fanless	Yes
Mean time between failures (MTBF)	1156942 h

Power

Power supply included	Yes
Number of power supply units	1
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	10 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 95%
Heat dissipation	32.86 BTU/h

Weight & dimensions

Width	215 mm
Depth	133 mm
Height	42 mm
Weight	900 g

Packaging content

Cables included	AC
Rack mount kit	Yes

Packaging data

Package type	Box
--------------	-----

Certificates

Certification	LVD, BSMI RoHS, REACH
---------------	-----------------------

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------