

Zyxel GS1200-5 Managed Gigabit Ethernet (10/100/1000) Silver

Gamintojas: ZYXEL · Modelis: GS1200-5-EU0101F · EAN: 4718937598670 · Prekės kodas: 652346



41,90 €

Kaina su PVM

Be PVM: 34,63 €

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed Web-based management IGMPv1,IGMPv2,IGMPv3
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 5
- ✓ MAC address table: 2000 entries Switching capacity: 10 Gbit/s



Aprašymas

Easy web management and set-up wizard

This switch comes with a user-friendly web-based set-up wizard that walks you through setup, configuration and management—including configuration backups and firmware upgrades—quickly and easily. With a few simple clicks, your network will be humming along, so you can get back to business.

IGMP Snooping for optimized traffic delivery

Based on the IGMP (Internet Group Management Protocol) query and report messages, the switch forwards traffic only to the ports that request the multicast traffic rather than to all ports. It helps to optimize multicast performance and is especially useful for bandwidth-intensive IP multicast applications such as online media streaming and gaming.

VLAN segregation for enhanced network security

VLAN (virtual local area network) can be used to separate traffic within a business such as isolating resources between network administrators and general users or between employees and public guest users.

Enhanced port-based QoS for better traffic control

QoS (Quality of service) is the ability to provide different priority to different applications, users, or video/voice/data flows, or to guarantee a certain level of performance to a data flow.

Link Aggregation increase throughput beyond what a single connection could sustain

GS1200-5/8 combines 2 physical ports together to make a single high-bandwidth data path, for faster file transfers and to enhance connection reliability.

Advanced energy-savings at work

This switch's built-in IEEE 802.3az Energy Efficient Ethernet (EEE) function automatically detects network traffic and adjusts power consumption dynamically to reduce power usage during times of low traffic.

Fanless, noiseless design

Extend your network control and visibility without disrupting your quiet business environment. This business switch features a fanless design that ensures noiseless operation and greater reliability over time with fewer parts to fail.

More comprehensive smart features included

Featuring Gigabit performance that's 10 times faster than Fast Ethernet. Deliver up to 2,000 Mbps of dedicated, non-blocking bandwidth per port and more advanced features like port mirroring, Jumbo Frame, broadcast storm control, loop detection/prevention. It's a great choice for SMBs who want to enjoy high-speed business network applications!

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Managed
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes

VLAN support	Yes
Data transmission	
MAC address table	2000 entries
Switching capacity	10 Gbit/s
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	1 MB
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Authentication	Auto VLAN, MAC-based authentication
Multicast features	
Multicast support	Yes
Protocols	
Management protocols	IGMPv1,IGMPv2,IGMPv3
Design	
Rack mounting	No
Product colour	Silver
LED indicators	Power
Safety	CE-LVD, BSMI
Electromagnetic compatibility	CE, FCC, BSMI, Class B
Performance	
Firmware upgradeable	Yes
Power	
DC input voltage	5 V
Input current	1 A
Power consumption (max)	2.03 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	121 mm
Depth	75 mm
Height	26 mm
Weight	233 g

Packaging content

Quick start guide	Yes
-------------------	-----

Packaging data

AC adapter included	Yes
Package type	Box
Rubber feet	Yes
Package width	127 mm
Package depth	82 mm
Package height	95 mm
Package weight	388 g

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------