

Zyxel GS1900-48-EU0102F network switch L2 Gigabit Ethernet (10/100/1000) Black

 Gamintojas: **ZYXEL** · Modelis: **GS1900-48-EU0102F** · EAN: **4718937621255** · Prekės kodas: **652357**


346,89 €

Kaina su PVM

 Be PVM: **286,69 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ L2
- ✓ Basic switching RJ-45 Ethernet ports quantity: 48
- ✓ MAC address table: 8000 entries Switching capacity: 100 Gbit/s
- ✓ Rack mounting



Aprašymas

Simple, Fast and Smart Managed Switches for Small Business Connectivity

The ZyXEL GS1900 Series of 8/16/24/48-port GbE Smart Managed Switch with Gigabit speed and essential managing functions bring your business network more flexibility and connectivity. The 1900 Series consists of eight (8) models—the GS1900-8, GS1900-8HP, GS1900-16, GS1900-24E, GS1900-24, GS1900-24HP, GS1900-48 and GS1900-48HP. Providing GbE switches with powersaving functions, fanless design and full IPv6 support ensure your network to be ready for future expansions. In addition, the PoE models GS1900-8HP/24HP/48HP Gigabit switch complies with the IEEE 802.3at Power over Ethernet (PoE) Plus standard. The complete GS1900 Series has been designed with useful features and advanced performances that empower your networks with speed and security as well as silent operation in your office environments.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switche [+1398][-565]

Management features

Switch layer

L2

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity

48

Basic switching RJ-45 Ethernet ports type

Gigabit Ethernet (10/100/1000)

SFP module slots quantity

2

Power connector

AC-in jack

Network

Networking standards

IEEE 802.1af, IEEE 802.1D, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x

10G support

No

Data transmission

MAC address table

8000 entries

Switching capacity

100 Gbit/s

Throughput

74 Mpps

Design

Rack mounting

Yes

Product colour

Black

Power over Ethernet (PoE)

Power over Ethernet (PoE)

No

Operational conditions

Operating temperature (T-T)

0 - 50 °C

Storage temperature (T-T)

-40 - 70 °C

Operating relative humidity (H-H)

10 - 95%

Heat dissipation

126 BTU/h

Weight & dimensions

Width

440 mm

Depth

200 mm

Height

44 mm

Weight

29 kg

Packaging data

Package width

509 mm

Package depth

292 mm

Package height	93 mm
Package weight	4.3 kg
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (l × P × A)	51,00cm × 10,00cm × 29,00cm