

LevelOne 24-Port Gigabit Switch

Gamintojas: **LEVELONE** · Modelis: **GSW-2457** · EAN: **4015867143124** · Prekės kodas: **652438**



160,91 €

Kaina su PVM

Be PVM: **132,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10/100BASE-TX UTP to 100BASE-FX copper to fiber media converter
- ✓ Supports 8K MAC address auto-learning and auto-aging
- ✓ 9K jumbo frames to increase data transfer rates
- ✓ 24 Gigabit Ethernet ports
- ✓ Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- ✓ 19-inch metal housing
- ✓ Fanless Design



Aprašymas

Gigabit Speeds: Take Your Data to the Next LevelGSW-2457 is a 24-port Gigabit Ethernet Switch that gives you a high-performance, low-cost, easy-to-use, seamless upgrade to boost your network to 1000Mbps. Increase the speed of your network backbone to a massive 48Gbps and bring lightning fast Gigabit connections to all your computers.Bandwidth hungry? Not a problem.What happens when you have several users accessing multimedia applications all at the same time? No need to worry as GSW-2457 allows you to move large files faster and easier. Transfer your CGI, CAD, video, or other large multimedia files over the network instantly and without lag.Plug and Play, Flexible and EasyGSW-2457 is plug-and-play so no configuration is required. Providing auto MDI/MDI-X cable detection on all ports eliminates the need for crossover cables or Uplink ports. Each port can be used as general ports or Uplink ports, and any port can be simply plugged into a server, a hub, a router or a switch, using a straight cable or crossover cable.

Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Netzwerk > Switche [+1398][-565]

Management features

Switch type Unmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity 24

Basic switching RJ-45 Ethernet ports type Gigabit Ethernet (10/100/1000)

Installed SFP modules quantity 0

Installed SFP+ modules quantity 0

Gigabit Ethernet (copper) ports quantity 24

Network

Networking standards IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u

10G support No

Auto MDI/MDI-X Yes

MAC address auto-learning supported Yes

MAC address auto-aging supported Yes

Data transmission

MAC address table 8000 entries

Switching capacity 48 Gbit/s

Forwarding rate 1.488 Mpps

Store-and-forward Yes

Jumbo frames support Yes

Jumbo frames 9000

Design

Rack mounting Yes

Product colour Black

Housing material Metal

LED indicators Activity, Link, Power, Speed

Performance

Built-in processor Yes

Flash memory 4 MB

Power

AC input voltage 100 - 240 V

AC input frequency 50 Hz

Power consumption (typical)	15 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	44 mm
Depth	220 mm
Height	440 mm
Weight	2.65 kg
Packaging content	
Cables included	AC
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Package width	224 mm
Package depth	486 mm
Package height	77 mm
Package weight	2.2 kg
Technical details	
Master (outer) cases per pallet layer	22 pc(s)
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet height (air)	155.5 cm
Logistics data	
Country of origin	China
Master (outer) case width	405 mm
Master (outer) case length	500 mm
Master (outer) case height	240 mm
Harmonized System (HS) code	85176990

Master (outer) case gross weight	12 kg
Products per master (outer) case	5 pc(s)