

LevelOne RJ45 to SFP Managed Gigabit Media Converter

Gamintojas: **LEVELONE** · Modelis: **GVM-1000** · EAN: **4015867195628** · Prekės kodas: **652457**



176,90 €

Kaina su PVM

Be PVM: **146,20 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 1000 Mbit/s
- ✓ 10BASE-T, 100BASE-TX, 1000BASE-T
- ✓ Ethernet LAN (RJ-45) ports: 1
- ✓ Fiber ports quantity: 1 SFP
- ✓ Black



Aprašymas

GVM-1000 series is remote Managed Gigabit Ethernet fiber media converter with OAM functions developed by our company. It can convert Ethernet signal between 10/100/1000Base-T and 1000Base-X, It supports both half-duplex and full-duplex operations and a variety of fiber options.

Remote devices can be managed by fiber-connected OAM media converter or OAM switch when deployed as a stand-alone solution. It incorporates an easy to use Web user interface for operation, administration and maintenance, both locally and remotely. By offering IEEE802.3ah OAM compliance, this converter can be linked to any IEEE802.3ah compliant fiber switch and support loop back and dying gasp functions. All functions of this converter and the remotely connected converter can be configured and monitored via Web management, including bandwidth control, duplex, speed and VLAN configuration.

Key Features

- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Web-based and SNMP Management

- Built-in LFP (Link Fault Pass-through) (LLCF/LLR) Technology
- Supports VLAN (tag-based, Q-in-Q)

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Jumbo frames support	Yes
Jumbo frames	9000
Flow control support	Yes
VLAN support	Yes
Store-and-forward	Yes
Duplex system	Full, Half
Link Loss Carry Forward (LLCF) supported	Yes
Link Loss Return (LLR) supported	Yes
Performance	
Mean time between failures (MTBF)	30000 h
Features	
Internal	No
Web-based management	Yes
Hot-swap	Yes
LED indicators	Activity, FDX, Link, Power
Product colour	Black
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Input voltage	100 - 240 V

Output voltage	5 V
Output current	2 A
Weight & dimensions	
Width	127 mm
Depth	156 mm
Height	32 mm
Weight	700 g
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	5 - 90%
Packaging content	
Manual	Yes
Packaging data	
Package width	185 mm
Package depth	275 mm
Package height	62 mm
Package weight	860 g
Certificates	
Compliance certificates	RoHS
Certification	CE, FCC
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990
Master (outer) case width	360 mm
Master (outer) case length	480 mm
Master (outer) case height	390 mm
Master (outer) case gross weight	17.5 kg
Products per master (outer) case	17 pc(s)