

LevelOne GVT-0500 network media converter 10000 Mbit/s Black

Gamintojas: **LEVELONE** · Modelis: **GVT-0500** · EAN: **4015867209301** · Prekės kodas: **652459**



252,90 €

Kaina su PVM

Be PVM: **209,01 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 9K jumbo frames to increase data transfer rates
- ✓ Supports low-time lag transmission
- ✓ Supports ITU-T DWDM/CWDM wavelengths
- ✓ Hot-swappable
- ✓ Quick and easy installation



Aprašymas

The LevelOne GVT-0500 is a powerful 10 Gigabit media converter which, in combination with the optional available LevelOne SFP+ modules, converts optical into electrical signals, supports optical signal equilibrium amplification, clock extraction and optical regeneration. It uses WDM (DWDM/CWDM) technology, which can transmit data signals over a long distance in a single fiber in simple or multiple ways. On existing network infrastructure, the GVT-0500 can quickly improve transmission capacity and expand bandwidth. At the same time, it is a cost-efficient and highly cost-effective solution for managing and operating the system. It is also optimized for ease of operation and maintenance.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switches [+1398][565]

Network

Maximum data transfer rate	10000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Ethernet interface type	10 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet
Ethernet LAN data rates	10,100,1000,10000 Mbit/s
Copper ethernet cabling technology	10BASE-T, 10GBASE-T, 100BASE-TX, 1000BASE-LX, 1000BASE-SX, 1000BASE-T
Fiber ethernet cabling technology	10GBASE-ER, 10GBASE-LR, 10GBASE-SR, 10GBASE-ZR
Jumbo frames support	Yes
Jumbo frames	9000
Auto MDI/MDI-X	Yes
Duplex system	Full
Cable types supported	Cat6a

Performance

Maximum transfer distance	100 m
Mean time between failures (MTBF)	50000 h

Features

Internal	No
Hot-swap	Yes
LED indicators	Activity, Link, Power
Product colour	Black
Housing material	Metal

Ports & interfaces

Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes

Power

Input voltage	5 V
Input current	3 A
Power consumption (typical)	1.2 W

Weight & dimensions

Width	115 mm
Depth	85 mm
Height	25 mm

Weight	300 g
--------	-------

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
-----------------------------	-------------

Storage temperature (T-T)	-40 - 75 °C
---------------------------	-------------

Operating relative humidity (H-H)	5 - 90%
-----------------------------------	---------

Packaging content

AC adapter included	Yes
---------------------	-----

Quick installation guide	Yes
--------------------------	-----

Packaging data

Package width	230 mm
---------------	--------

Package depth	150 mm
---------------	--------

Package height	85 mm
----------------	-------

Package weight	700 g
----------------	-------

Package type	Box
--------------	-----

Certificates

Compliance certificates	RoHS
-------------------------	------

Certification	CE
---------------	----

Logistics data

Country of origin	China
-------------------	-------

Harmonized System (HS) code	85176990
-----------------------------	----------