

LevelOne RJ45 to SFP Gigabit Media Converter, PoE PD

Gamintojas: **LEVELONE** · Modelis: **GVT-2010** · EAN: **4015867195192** · Prekės kodas: **652464**



151,90 €

Kaina su PVM

Be PVM: **125,54 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 100BASE-TX, 1000BASE-T
- ✓ 1000BASE-LX, 1000BASE-SX
- ✓ Ethernet LAN (RJ-45) ports: 1
- ✓ Fiber ports quantity: 1 SFP
- ✓ Black



Aprašymas

GVT-2010 10/100/1000Mbps adaptive Gigabit Ethernet media converter adopts switching technology to fulfill media conversion. It complies with IEEE802.3, IEEE802.3u, IEEE802.3z and IEEE802.3ab standards. Presently it supports two types of media network connections: 10Base-T/100Base-TX/1000Base-T, and 1000Base-SX/LX, inter-converting electrical signals of 10Base-T/100Base-TX/1000Base-T twisted pairs with optical signals of 1000Base-SX/LX. It extends the transmission distance of network from 100m via copper cable to 100 km via fiber optical cable.

GVT-2010 supports 802.3at/af POE-PD function. It can draw the power via UTP cable connect to a POE-PSE switch or mid-span injector. This function makes the GVT-2010 ideal for remote areas of a network without power outlets

Key Features

- Transfers data from 10/100/1000Base-T copper to fiber interfaces
- SFP slot supports pluggable Gigabit optic modules that enabling you to choose from a variety of transceiver
- 9K jumbo frames to increase data transfer rates

- Built-in LFP (Link Fault Pass-through) (LLCF/LLR) Technology
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Supports low-time lag transmission
- Supports the transmission of extra-long packets up to 1.6KB
- 10°C to 55°C operating temperature range
- IEEE 802.3af/at PoE compliant to simplify deployment and installation

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Ethernet LAN data rates	10,100,1000 Mbit/s
Copper ethernet cabling technology	100BASE-TX, 1000BASE-T
Fiber ethernet cabling technology	1000BASE-LX, 1000BASE-SX
Jumbo frames support	Yes
Jumbo frames	9000
Flow control support	Yes
VLAN support	Yes
Auto MDI/MDI-X	Yes
Store-and-forward	Yes
Duplex system	Full, Half
Performance	
Mean time between failures (MTBF)	30000 h
Features	
Internal	No
Web-based management	Yes
LED indicators	Activity, FDX, Link, Power
Product colour	Black
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power over Ethernet plus (PoE+) ports quantity	1

Power

Input voltage	90 - 264 V
Output voltage	5 V
Output current	2 A

Weight & dimensions

Width	94 mm
Depth	71 mm
Height	26 mm
Weight	220 g

Operational conditions

Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 90%

Packaging content

Manual	Yes
--------	-----

Packaging data

Package width	120 mm
Package depth	55 mm
Package height	235 mm
Package weight	430 g

Certificates

Compliance certificates	RoHS
Certification	CE, FCC

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------