

LevelOne RJ45 to SFP Gigabit Media Converter Switch, 2 x SFP, 1 x RJ45

Gamintojas: **LEVELONE** · Modelis: **GVT-2011** · EAN: **4015867202517** · Prekės kodas: **652465**



121,90 €

Kaina su PVM

Be PVM: **100,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 1000 Mbit/s
- ✓ 10BASE-T, 100BASE-TX, 1000BASE-T
- ✓ Ethernet LAN (RJ-45) ports: 1 DC-in jack
- ✓ Fiber ports quantity: 2 SFP
- ✓ Grey



Aprašymas

The LevelOne GVT-2011 Gigabit Media Converter Switch provides 1 RJ45 and 2 SFP ports to support conversion between 10/100/1000Base-T and 1000Base-X networks. With the two SFP ports, the converter switch provides high reliability and flexibility to extend the media transmission distance up to 550m, 20km, or longer depending on the SFP fiber optical transceivers. It allows the two types of segment to connect easily, efficiently and inexpensively.

The GVT-2011 works in high performance Store and Forward mechanism, and prevent packet loss with IEEE 802.3x Flow Control (Full-Duplex) and Back Pressure (Half-Duplex) functions. As the GVT-2011 Media Converter fully complies with IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T and IEEE 802.3z 1000Base-X, the Gigabit media converter installation is quite quick and easy by simply plug and play.

- Transfers data from 10/100/1000Base-T copper to fiber interfaces
- SFP slot supports pluggable Gigabit optic modules that enabling you to choose from a variety of transceiver

- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Supports low-time lag transmission
- 10°C to 55°C operating temperature range

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Maximum data transfer rate	1000 Mbit/s
Converter input interface	10Base-T, 100Base-TX, 1000Base-T
Converter output interface	1000Base-X
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Jumbo frames support	Yes
Jumbo frames	9000
Flow control support	Yes
VLAN support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Store-and-forward	Yes
Duplex system	Full, Half
Performance	
Mean time between failures (MTBF)	30000 h
Features	
Internal	No
LED indicators	Activity, Link, Power
Product colour	Grey
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	2
DC-in jack	Yes

Power

Input voltage	110 - 240 V
Output voltage	5 V
Output current	2 A
Power consumption (max)	5 W

Weight & dimensions

Width	71 mm
Depth	94 mm
Height	26 mm
Weight	300 g

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	5 - 90%

Packaging content

AC adapter included	Yes
Quick installation guide	Yes

Packaging data

Package width	120 mm
Package depth	235 mm
Package height	55 mm
Package weight	380 g
Package type	Box

Certificates

Certification	FCC, CE
---------------	---------

Logistics data

Country of origin	China
Harmonized System (HS) code	85176990
Master (outer) case width	360 mm
Master (outer) case length	480 mm
Master (outer) case height	390 mm
Master (outer) case gross weight	1.2 kg
Products per master (outer) case	36 pc(s)