

LevelOne HDMI over Cat.5 Transmitter, HDBaseT, 100m, 4 Channel Outputs, 802.3af PoE

Gamintojas: **LEVELONE** · Modelis: **HVE-9214PT** · EAN: **4015867193006** · Prekės kodas: **652682**



875,89 €

Kaina su PVM

Be PVM: **723,88 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ AV transmitter 3840 x 2160 pixels
- ✓ Maximum transfer distance: 100 m
- ✓ 7.1 channels
- ✓ HDCP
- ✓ DC-in jack



Aprašymas

The HVE-92 series is a HDMI extension solution supports HDBaseT technology which transmits HDMI signal and multi-channel audio at resolution Ultra HD 4K x 2K (3840 x 2160 @ 30Hz) and 1080p Full HD up to 100m via Cat5e or Cat6 cable.

The series of products are embedded with EDID priority management of HDMI outputs supports EDID Hotplug refreshing function. These products also provide Bi-Directional RS-232 and IR to control the connected devices from either source or display location.

All the features are made to simplify installation and reduce costs, but at the same time providing exceptional video and audio quality. The HVE-92 series is the perfect solution for Digital Signage, trade shows, home theater installations, medical facilities, and other public exhibitions.

Key Features

- IEEE 802.3af PoE compliant to simplify deployment and installation

- Simple Plug and Play installation
- Built-in EDID Hot Plug Detection (HPD)
- HDMI outputs with EDID management
- Transmission distance of up to 100m for HDMI(4k2k), IR and RS-232
- Bi-Directional RS-232 pass through & IR Control
- Supports video resolutions up to 3840 x 2160 (4K x 2K) @ 30Hz
- HDMI and HDCP complaint
- Supports Dolby TrueHD, DTS-HD Master Audio, Dolby Digital Plus, LPCM 7.1 audio
- Supports 3D, CEC & Lip Sync pass-through
- Screw-in power socket for added safety

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Features	
Type	AV transmitter
Maximum resolution	3840 x 2160 pixels
Cable types supported	Cat5e, Cat6
Maximum transfer distance	100 m
Audio system	Multichannel
Audio output channels	7.1 channels
LED indicators	Link, PoE, Power
Supported video modes	1080p
Bandwidth	10.2 Gbit/s
HDCP	Yes
Material	Metal
Colour depth	36 bit
3D	Yes
HDCP & EDID bypass	Yes
Consumer Electronics Control (CEC) support	Yes
Carrier frequency	38 kHz
Baud rate	115.2 Kbit/s
Plug and Play	Yes
Networking standards	IEEE 802.3af
Ports & interfaces	
RJ-45 output ports	4
HDMI in	1
Number of HDMI outputs	1

RS-232 input ports	1
3.5 mm (1/8-inch) in	Yes
3.5 mm (1/8-inch) out	Yes
DC-in jack	Yes
Power	
Operating voltage	12 V
Power consumption (transmitter) (max)	5000 mA
Current	6.6 A
Power over Ethernet (PoE)	Yes
Weight & dimensions	
Width	300 mm
Depth	160 mm
Height	44 mm
Weight	380 g
Transmitter dimensions (WxDxH)	300 x 160 x 44 mm
Transmitter weight	1.27 kg
Packaging data	
Package dimensions (WxDxH)	280 x 160 x 120 mm
Package width	280 mm
Package depth	160 mm
Package height	120 mm
Package weight	2.25 kg
Package type	Box
Packaging content	
AC adapter included	Yes
Cables included	AC
Manual	Yes
Remote control included	Yes
Technical details	
Country of origin	Taiwan