

LevelOne 5-Port Fast Ethernet Industrial Switch, DIN-Rail, 1 x SC Multi-Mode Fiber, -20°C to 70°C

Gamintojas: **LEVELONE** · Modelis: **IES-0510** · EAN: **4015867181607** · Prekės kodas: **652797**



204,90 €

Kaina su PVM

Be PVM: **169,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 4
- ✓ 10BASE-T, 100BASE-TX
- ✓ MAC address table: 2048 entries

Aprašymas

LevelOne IES-0510 Industry Ethernet Switch provides 4 ports of 10/100Base-TX Ethernet plus 1 port 100FX Multimode SC fiber to enable high speed network at mission-critical environment. This device is designed to be mounted on an industry standard DIN-rail, plus the clearly visible status LEDs provide simple monitoring of port link activity.

Cost Effective

This device operates under -10 to 60 Celsius (-14 to 140 Fahrenheit) temperature that offers optimal suitability for industrial applications at low cost while maintaining all components built to withstand harsh environment applications without compromise reliability and stability.

Safety

With UL60950 standard complied that gives basic protection against electric shock, fire spread from within, ignition and burning, current circuit hazardous under normal and fault condition. As well as set of compliances to meet many EMC, isolation, vibration and shock standards.

Plug & Play

This device is designed for the demanding industrial environments at businesses in need of instant connectivity with no setup or configure required, truly plug and play.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Unmanaged
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	4
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Fiber optic connector	SC
Network	
Networking standards	IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Full duplex	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Optical fiber	
Fiber ethernet cabling technology	100BASE-FX
Fiber type	Multi-mode
Data transmission	
MAC address table	2048 entries
Store-and-forward	Yes
Packet forwarding rate (100 Mbps)	148810 pps
Packet forwarding rate (10 Mbps)	14880 pps
Packet buffer memory	0.384 MB
Design	
Product colour	Black
Housing material	Plastic
LED indicators	Activity, Link, Speed
International Protection (IP) code	IP30
Safety	UL60950-1

Performance

Mean time between failures (MTBF)	1071085 h
-----------------------------------	-----------

Power

Input voltage	12 - 48 V
---------------	-----------

Power consumption (max)	4.3 W
-------------------------	-------

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	-10 - 60 °C
-----------------------------	-------------

Storage temperature (T-T)	-25 - 85 °C
---------------------------	-------------

Operating relative humidity (H-H)	5 - 95%
-----------------------------------	---------

Weight & dimensions

Width	26 mm
-------	-------

Depth	70 mm
-------	-------

Height	110 mm
--------	--------

Weight	200 g
--------	-------

Packaging content

Quick start guide	Yes
-------------------	-----

Packaging data

Package type	Box
--------------	-----

Package width	180 mm
---------------	--------

Package depth	79 mm
---------------	-------

Package height	221 mm
----------------	--------

Package weight	460 g
----------------	-------

Certificates

Certification	ISO9001 FCC Part 15 EN61000-6-4 EN55022 EN61000-3-2 EN61000-3-3 EN61000-6-2 EN61000-4-2 EN61000-4-3 EN61000-4-4 EN61000-4-5 EN61000-4-6 EN61000-4-8 IEC60068-2-6 Fc IEC60068-2-27 Ea IEC60068-2-32 Ed
---------------	---

Logistics data

Country of origin	Taiwan
-------------------	--------

Harmonized System (HS) code	85176990
-----------------------------	----------