

LevelOne 5-Port Fast Ethernet Industrial Switch, -40°C to 75°C

Gamintojas: **LEVELONE** · Modelis: **IFS-0501** · EAN: **4015867192283** · Prekės kodas: **652807**



83,90 €

Kaina su PVM

Be PVM: **69,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Basic switching RJ-45 Ethernet ports quantity: 5
- ✓ 10BASE-T, 100BASE-TX
- ✓ MAC address table: 1024 entries Switching capacity: 1 Gbit/s



Aprašymas

The LevelOne IFS-0501 Industrial Fast Ethernet Switch provides 5 ports at 10/100M TX to enable high speed network in mission-critical environments. With an industrial standard DIN-rail mount, this switch can be installed in a cabinet, and clearly visible status LEDs provide simple monitoring of port link activity. The switch is housed in a solid metal case rated at IP30, keeping it safe from dust, vibration, heat and humidity, while an operational temperature range of -40°C to +75°C makes it suitable for deployment in almost any environment.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switches [+1398][-565]

Management features

Switch type

Unmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0

Network

Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Full duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes

Data transmission

MAC address table	1024 entries
Switching capacity	1 Gbit/s
Store-and-forward	Yes
Packet forwarding rate (100 Mbps)	148000 pps
Packet forwarding rate (10 Mbps)	14880 pps
Packet buffer memory	1 MB

Design

Rack mounting	No
Product colour	Black
Housing material	Metal
LED indicators	Link, Power
International Protection (IP) code	IP30
Wall mountable	Yes
Safety	EN60950-1

Performance

Internal memory	1 MB
Maximum data transfer rate	100 Mbit/s

Power

Output voltage	24 V
Output current	1 A

Power consumption (typical)	3.76 W
-----------------------------	--------

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	-40 - 75 °C
-----------------------------	-------------

Storage temperature (T-T)	-40 - 85 °C
---------------------------	-------------

Operating relative humidity (H-H)	5 - 95%
-----------------------------------	---------

Storage relative humidity (H-H)	5 - 95%
---------------------------------	---------

Weight & dimensions

Width	36 mm
-------	-------

Depth	105 mm
-------	--------

Height	142 mm
--------	--------

Weight	470 g
--------	-------

Packaging content

Quick start guide	Yes
-------------------	-----

Packaging data

Wall mounting kit	Yes
-------------------	-----

Terminal block included	Yes
-------------------------	-----

Package type	Box
--------------	-----

Package width	65 mm
---------------	-------

Package depth	165 mm
---------------	--------

Package height	215 mm
----------------	--------

Package weight	180 g
----------------	-------

Certificates

Certification	FCC, CE, RoHS, VCCI EN55022/24 EN55011 EN50121-3-2 EN50121-4 (pending) EN50155 (pending) EN60068-2-6 EN60068-2-27 EN60068-2-32
---------------	---

Logistics data

Country of origin	Taiwan
-------------------	--------

Harmonized System (HS) code	85176990
-----------------------------	----------