

# LevelOne RJ45 to SFP Gigabit Industrial Media Converter, 1 PoE Output

Gamintojas: **LEVELONE** · Modelis: **IGC-0101** · EAN: **4015867203910** · Prekės kodas: **652809**



## 127,90 €

Kaina su PVM

Be PVM: **105,70 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 9K jumbo frames to increase data transfer rates
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ 40°C to 75°C operating temperature range
- ✓ Supports DIN-rail installation



## Aprašymas

This IGC-0101 Industrial POE media converter is equipped with Hardened Marvell IC to provide a reliable power source to power up your remote POE device. It is designed for Security, Transportation and Telco application to extend your network distances. With its multi-purpose design, it can also be used for Din-Rail or wall-mounted. It is an ideal unit for IP surveillance, traffic monitoring and Security application in critical environment. It can tolerate -40°C to 75°C in harsh environment to perform a reliable network.

## Techninė specifikacija

### Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

**Network**

|                                    |                                                                                             |
|------------------------------------|---------------------------------------------------------------------------------------------|
| Maximum data transfer rate         | 1000 Mbit/s                                                                                 |
| Networking standards               | IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z |
| Ethernet interface type            | Gigabit Ethernet                                                                            |
| Ethernet LAN data rates            | 10,100,1000 Mbit/s                                                                          |
| Copper ethernet cabling technology | 10BASE-T, 100BASE-TX, 1000BASE-T                                                            |
| Jumbo frames support               | Yes                                                                                         |
| Jumbo frames                       | 9000                                                                                        |
| Flow control support               | Yes                                                                                         |

**Performance**

|                                   |          |
|-----------------------------------|----------|
| Mean time between failures (MTBF) | 500000 h |
|-----------------------------------|----------|

**Features**

|                   |                       |
|-------------------|-----------------------|
| Internal          | No                    |
| LED indicators    | Activity, Link, Power |
| DIN rail mounting | Yes                   |

**Ports & interfaces**

|                                          |       |
|------------------------------------------|-------|
| Fiber optic connector                    | SFP   |
| Connectivity technology                  | Wired |
| Ethernet LAN (RJ-45) ports               | 1     |
| Fiber ports quantity                     | 1     |
| Power over Ethernet (PoE) ports quantity | 1     |

**Power**

|                                        |           |
|----------------------------------------|-----------|
| Input voltage                          | 48 - 56 V |
| Power consumption (typical)            | 2 W       |
| Power over Ethernet (PoE)              | Yes       |
| Total Power over Ethernet (PoE) budget | 30 W      |

**Weight & dimensions**

|        |          |
|--------|----------|
| Width  | 32 mm    |
| Depth  | 81.5 mm  |
| Height | 103.5 mm |
| Weight | 135 g    |

**Operational conditions**

|                             |             |
|-----------------------------|-------------|
| Operating temperature (T-T) | -40 - 75 °C |
|-----------------------------|-------------|

|                                   |         |
|-----------------------------------|---------|
| Operating relative humidity (H-H) | 5 - 95% |
|-----------------------------------|---------|

#### Packaging content

|        |     |
|--------|-----|
| Manual | Yes |
|--------|-----|

#### Packaging data

|               |        |
|---------------|--------|
| Package width | 165 mm |
|---------------|--------|

|               |       |
|---------------|-------|
| Package depth | 65 mm |
|---------------|-------|

|                |        |
|----------------|--------|
| Package height | 215 mm |
|----------------|--------|

|                |       |
|----------------|-------|
| Package weight | 350 g |
|----------------|-------|

#### Certificates

|        |               |
|--------|---------------|
| Safety | IEC EN60950-1 |
|--------|---------------|

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| Certification | CE, FCC, VCCI, FCC Part 15 Subpart B Class A, CE EN 55022 Class A |
|---------------|-------------------------------------------------------------------|

#### Logistics data

|                   |        |
|-------------------|--------|
| Country of origin | Taiwan |
|-------------------|--------|

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 85176990 |
|-----------------------------|----------|

|                           |        |
|---------------------------|--------|
| Master (outer) case width | 350 mm |
|---------------------------|--------|

|                            |        |
|----------------------------|--------|
| Master (outer) case length | 240 mm |
|----------------------------|--------|

|                            |        |
|----------------------------|--------|
| Master (outer) case height | 560 mm |
|----------------------------|--------|

|                                  |        |
|----------------------------------|--------|
| Master (outer) case gross weight | 6.6 kg |
|----------------------------------|--------|

|                                  |          |
|----------------------------------|----------|
| Products per master (outer) case | 16 pc(s) |
|----------------------------------|----------|