

LevelOne Industrial Gigabit PoE Injector, 36W, 802.3at/af PoE

Gamintojas: **LEVELONE** · Modelis: **IGP-0101** · EAN: **4015867196045** · Prekės kodas: **652810**



178,90 €

Kaina su PVM

Be PVM: **147,85 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10,100,1000 Mbit/s
- ✓ Black
- ✓ Power over Ethernet (PoE) IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u



Aprašymas

The LevelOne IGP-0101 is rugged designed 30 Watts, high power Single port industrial POE Injector is equipped with our high efficiency ColdDesign technology to provide 30 Watts power to your security equipment. The ColdDesign technology will not only power up your PD device, also reduce the excessive heat problem to a minimum. It accepts the input voltage from 48~56 VDC to deliver 30Watts power to meet IEEE802.3af/at standard. It is being rigorously tested for your Security, Transportation and Telco application.

Key Features

- PoE ports can support the IEEE 802.3at standard and power up 30W devices
- 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- 40°C to 75°C operating temperature range
- Provides DIN-rail, wall or desktop mounting
- IP30 metal case
- Redundant power inputs with Terminal Block

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u
Duplex system	Full
Features	
Product colour	Black
Wall mountable	Yes
LED indicators	PoE, Power
Safety	EN60950-1Ç EN55022/24, EN50155, EN55011, EN50121-3-2 EN60068-2-7, EN60068-2-27, EN60068-2-32
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
Power	
Power over Ethernet (PoE) voltage	56 V
Output power	36 W
Certificates	
Certification	CE, FCC, RoHS, VCCI
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-40 - 85 °C
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	81.5 mm
Depth	32 mm
Height	103.5 mm
Weight	140 g
Packaging content	
Manual	Yes

Packaging data

Package width	165 mm
Package depth	65 mm
Package height	215 mm
Package weight	370 g

Logistics data

Harmonized System (HS) code	85044095
-----------------------------	----------