

LevelOne Hilbert 28-Port Industrial Gigabit Smart Lite Switch, 24x RJ45, 4x SFP/RJ45 Combo

Gamintojas: **LEVELONE** · Modelis: **IGS-2128** · EAN: **4015867236222** · Prekės kodas: **652830**



457,90 €

Kaina su PVM

Be PVM: **378,43 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24 Gigabit Ethernet ports and 4 Gigabit SFP/RJ45 Combo
- ✓ Web-based and smart lite Management
- ✓ Supports LevelOne IP Locator for easier IP management.
- ✓ Supports 8K MAC address auto-learning and auto-aging
- ✓ 9K jumbo frames to increase data transfer rates
- ✓ IP Multicast Filtering through IGMP Snooping V1 / V2
- ✓ 802.1Q tag-based VLAN allows network segmentation to enhance performance and security
- ✓ IEEE 802.1p QoS with 4 priority queues
- ✓ Supports unknown unicast / broadcast / multicast storm control
- ✓ Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)



Aprašymas

The LevelOne IGS-2128 Hilbert Industrial gigabit smart lite switch is a next-generation Ethernet Switch offering powerful better functionality and usability that delivers the cost-effectively business and transports Ethernet services via fiber or copper connections. IGS-2128 delivers 24 (10M/100M/1G) RJ45 ports and 4 Combo GbE RJ45/SFP ports. With the standard 19" Rack mount, plus the clearly visible status LEDs provide simple monitoring of port link activity.. can be matched with the latest LevelOne IP Locator, the software is the easiest to use switch discovery tool, it can search all Hilbert series switches, instantly know the forgotten IP and other info. Compatible with mainstream Windows and Mac operating systems.

The LevelOne IGS-2128 provides high HW performance and environment flexibility for Enterprises. IGS-2128 is ideal to deliver management simplicity, optimum user experience, and lower total cost of ownership.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	28
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	24
Combo SFP ports quantity	4
Network	
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN, Tagged VLAN
Number of VLANs	32
Data transmission	

MAC address table	8000 entries
Switching capacity	56 Gbit/s
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	4.1 MB
Security	
IGMP snooping	Yes
Queue scheduling algorithms	Priority queuing (PQ)
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Product colour	Black
LED indicators	Power, Link, Activity
International Protection (IP) code	IP30
Performance	
Flash memory	2 MB
Noise level	0 dB
Fanless	Yes
Mean time between failures (MTBF)	43800 h
Power	
Power source	DC
Power supply included	No
Redundant power supply (RPS) support	Yes
DC input voltage	12 - 57 V
Power consumption (typical)	20 W
Surge protection	Yes
Surge protection voltage	4 kV
Power protection features	Surge protection
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	-40 - 85 °C

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 95%
Heat dissipation	68.24 BTU/h
Weight & dimensions	
Width	440 mm
Depth	244 mm
Height	45 mm
Weight	3.4 kg
Packaging content	
Quick start guide	Yes
Rack mount kit	Yes
Packaging data	
Terminal block included	Yes
Package type	Box
Package width	510 mm
Package depth	375 mm
Package height	93 mm
Package weight	4 kg
Technical details	
Layers per pallet (air)	16 pc(s)
Pallet gross length	80 cm
Pallet gross width	120 cm
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS, UKCA
Logistics data	
Pallet gross height	174.4 cm
Country of origin	China
Master (outer) case width	540 mm
Master (outer) case length	320 mm
Master (outer) case height	400 mm
Harmonized System (HS) code	8517620090
Master (outer) case gross weight	12.5 kg
Products per master (outer) case	3 pc(s)
Sustainability	

Sustainability compliance

Yes