

TP-Link LiteWave LS106LP network switch Unmanaged Fast Ethernet (10/100) Power over Ethernet (PoE) Black

Gamintojas: **TP-LINK** · Modelis: **LS106LP** · EAN: **4895252504606** · Prekės kodas: **653403**



51,90 €

Kaina su PVM

Be PVM: **42,89 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 6
- ✓ Cat3, Cat4, Cat5, Cat5e 10BASE-T, 100BASE-TX
- ✓ MAC address table: 2000 entries Switching capacity: 1.2 Gbit/s
- ✓ DC/PoE Power supply included Power over Ethernet (PoE)



Aprašymas

- 41 W PoE Budget: Four 10/100 Mbps 802.3af-compliant PoE ports easily connect and power fixed devices like IP cameras, access points, and IP phones via a single cable. Up to 15.4 W PoE output is supported by each PoE port.*
- Up to 250 m PoE Transmission: With Extend Mode, PoE transmission distance reaches up to 250m, perfect for surveillance camera deployment in large areas.**
- PoE Auto Recovery: Automatically reboots your dropped or unresponsive PoE-powered devices.
- Plug and Play: Simply plug and play for instant connectivity with no configuration required.
- Silent Operation: Fanless design reduces power consumption and ensures silent operation, ideal for noise-sensitive homes or businesses.
- Reliable Hardware Design: Durable metal casing and desktop/wall-mounting design are well-suited for different environments.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Unmanaged
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	6
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Network	
Networking standards	IEEE 802.3af, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Data transmission	
MAC address table	2000 entries
Switching capacity	1.2 Gbit/s
Forwarding rate	0.8928 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Design	
Product colour	Black
LED indicators	Yes
Wall mountable	Yes
Number of fans	0 fan(s)
Performance	
Fanless	Yes
Power	

Power source	DC/PoE
Power supply included	Yes
AC input voltage	220 V
AC input frequency	50 Hz
DC input voltage	53.5 V
Input current	0.81 A
Power consumption (max)	47.76 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	4
Power over Ethernet (PoE) power per port	15.4 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	162.38 BTU/h
Weight & dimensions	
Width	158 mm
Depth	101 mm
Height	25 mm
Packaging content	
User guide	Yes
Packaging data	
Package type	Box
Certificates	
Certification	CE, FCC, RoHS
Matmenys ir svoris	
Matmenys (I × P × A)	10,00cm × 19,00cm × 14,00cm