

TP-Link LiteWave 10-Port Gigabit Desktop Switch with 8-Port PoE+

Gamintojas: **TP-LINK** · Modelis: **LS1210GP** · EAN: **4895252504576** · Prekės kodas: **653408**



100,90 €

Kaina su PVM

Be PVM: **83,39 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Full Gigabit Ports: 9× gigabit auto-negotiation RJ45 Ethernet ports and 1× gigabit SFP port provide up to 20 Gbps switching capacity
- ✓ 61 W PoE Budget: Eight gigabit 802.3af/at-compliant PoE+ ports easily connect and power fixed devices like IP cameras, access points, and IP phones via a single cable. Up to 30 W PoE output is supported by each PoE port.*
- ✓ Up to 250 m PoE Transmission: With Extend Mode, PoE transmission distance reaches up to 250m, perfect for surveillance camera deployment in large areas.**
- ✓ PoE Auto Recovery: Automatically reboots your dropped or unresponsive PoE-powered devices
- ✓ Traffic Separation for Higher Security: Isolation Mode allows one-click client traffic separation to avoid snooping and tampering, and isolate broadcast storm
- ✓ Plug and Play: Simply plug and play for instant connectivity with no configuration required
- ✓ Silent Operation: Fanless design reduces power consumption and ensures silent operation, ideal for noise-sensitive homes or businesses
- ✓ Reliable Hardware Design: Durable metal casing and desktop/wall-mounting design are well-suited for different environments



Aprašymas

Overview

The TP-Link LiteWave Series PoE Switches require no configuration and provide PoE (Power over Ethernet) ports. They can automatically detect and

supply power with all IEEE 802.3af/at compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Management features	
Switch type	Unmanaged
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	9
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP module slots quantity	1
Network	
Networking standards	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Data transmission	
MAC address table	4000 entries
Switching capacity	20 Gbit/s
Forwarding rate	14.88 Mpps
Store-and-forward	Yes
Jumbo frames	16000
Design	
Product colour	Black
LED indicators	Yes
Power	
Power source	DC/PoE

Power supply included	Yes
AC input voltage	220 V
AC input frequency	50 Hz
DC input voltage	53.5 V
Power consumption (max)	76.96 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	61 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	261.66 BTU/h
Weight & dimensions	
Width	209 mm
Depth	126 mm
Height	26 mm
Packaging content	
User guide	Yes
Packaging data	
Package type	Box
Certificates	
Certification	CE, FCC, RoHS