

Zyxel NWA210BE 11530 Mbit/ai Balta Maitinimas per Eternetą (PoE)

Gamintojas: **ZYXEL** · Modelis: **NWA210BE-EU0101F** · EAN: **4718937638772** · Prekės kodas: **654177**



315,89 €

Kaina su PVM

Be PVM: **261,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2,4 GHz 688 Mbit/ai
- ✓ 5 GHz 8646 Mbit/ai
- ✓ 6 GHz 11530 Mbit/ai
- ✓ Didžiausias duomenų perdavimo greitis: 11530 Mbit/ai
- ✓ IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x
- ✓ WEP, WPA, WPA2, WPA3
- ✓ Maitinimas per Eternetą (PoE)
- ✓ Antenų kiekis: 4 Vidinis Integruota antena



Aprašymas

Empowering the Modern, Connected Office with WiFi 7

Introducing the NWA210BE: a high-performance access point with BandFlex radio design, harnessing the full capabilities of WiFi 7. It combines easy setup, flexibility, and high speeds to empower today's modern, connected offices.

Ultra-fast WiFi 7 Speeds with Boosted Performance

NWA210BE - The BE12300 is a dual-radio access point with 2x2:2 at 2.4GHz and 4x4:4 at 5 or 6GHz, providing ultra-fast WiFi 7 speeds of up to 12.3Gbps to boost coverage range and enhance performance.

Flexible BandFlex Design

Dual-radio BandFlex design supports either 5GHz or 6GHz by configuration, fitting seamlessly into existing 5GHz coverage while futureproofing for 6GHz.

RF First by Design

The advanced RF filter design prevents 5GHz and 6GHz band interference, while the built-in 4G/5G interference filter allows seamless coexistence with cellular networks.

Flexible Management

NebulaFlex allows users to switch between standalone and intelligent Nebula cloud-managed modes as needed.

Dual 2.5GbE mGig Connectivity

Dual 2.5GbE ports unlock speeds beyond gigabit, providing a cost-effective upgrade to enjoy WiFi 7 performance while seamlessly integrating with existing infrastructure and offering remarkable flexibility to tailor both ports to fit your networking needs.

Connected - In Just a Few Clicks!

You can be connected in minutes with just a few simple clicks on the Nebula mobile app. The easy step-by-step wizard guides you through the entire installation process, and the intuitive app makes it easy to change settings as needed.

Nebula, The Intelligent Cloud Management

Nebula offers comprehensive monitoring and reporting capabilities, including real-time notifications for critical events via email or the mobile app.

With Nebula, you can enjoy a streamlined experience for network installation and management without the need for additional costs for software or hardware controllers.

Enhance Your WiFi with Nebula

Nebula automates wireless network management and optimization with features like WiFi Aid and Wireless Health, ensuring the best possible user experience. These features enhance network performance and reliability, delivering an exceptional WiFi experience.

Smooth and Secure Wireless Experience

The Connect & Protect service is a Nebula-cloud mode service focused on SB hotspot WiFi scenarios. It protects network users from cybersecurity threats and supports application-level network visibility and bandwidth throttling.

Ready to Boost Network Speeds Up to 2.5x

Paired with Zyxel NWA210BE WiFi 7 AP, the XMG1915-10EP/18EP switch is the perfect choice for upgrading your SB/SMB network's speed and performance, offering up to 2.5 times faster speeds than today's Gigabit networks.

With this switch, it's a breeze to boost your network speed using your existing wiring infrastructure without costly and disruptive cable upgrades.

Techninė specifikacija

Savybės	
2,4 GHz	Taip
5 GHz	Taip
6 GHz	Taip
Didžiausias duomenų perdavimo greitis	11530 Mbit/ai
Maksimalus duomenų perdavimo greitis (2,4 GHz)	688 Mbit/ai
Maksimalus duomenų perdavimo greitis (5 GHz)	8646 Mbit/ai
Didžiausia duomenų perdavimo sparta (6 GHz)	11530 Mbit/ai
Eterneto LAN duomenų perdavimo norma	10,100,1000,2500 Mbit/ai
Tinklo standartai	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x
Kabelių technologija	10/100/1000Base-T(X)
MIMO	Taip
VLAN palaikymas	Taip
Saugumas	
Apsaugos algoritmų palaikymas	WEP, WPA, WPA2, WPA3
Valdymo funkcijos	
Web pagrįstas valdymas	Taip
Firmware tobulinimas	Taip
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	2
USB 2.0 portų kiekis	1
USB jungtis	C tipo USB
WAN portas	Ethernet (RJ-45)
RS-232 sąsaja	Ne
DC įėjimo lizdas	Taip
Energijos valdymas	

Maitinimas per Eternetą (PoE)	Taip
Palaikomas maitinimo per eternetą (en. PoE) tipas	Active PoE
DC įtampos stiprumo intervalas	15 V
Įvesties srovė	2 A
Galios suvartojimas (maks.)	21,5 W
Konstrukcija	
Talpinimo	Lubos
Produkto spalva	Balta
Korpuso medžiaga	Polikarbonatas (PC)
On/off mygtukas	Ne
Atstatymo mygtukas	Taip
WPS paspaudžiamasis mygtukas	Ne
LED indikatoriai	Duomenys, PoE, Energija, WLAN
Antena	
Antenos tipas	Vidinis
Antenos krypties tipas	Nekryptinis
Antenos ypatybės	Integruota antena
Antenų kiekis	4
Antenos stiprinimo lygis (max)	3,17 dBi
Veikimo charakteristikos	
Integruotas procesorius	Taip
Svoris ir matmenys	
Plotis	250 mm
Ilgis	160 mm
Aukštis	47 mm
Svoris	815 g
Pakuotės duomenys	
Pakuotės plotis	279,5 mm
Pakuotės gylis	180,5 mm
Pakuotės aukštis	66 mm
Paketo svoris	1,04 kg
Aplinkos sąlygos	
Darbo santykinės drėgmės diapazonas	10 - 95%
Darbo temperatūros diapazonas (TT)	0 - 50 °C

Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
---------------------------------------	-------------

Sandėliavimo santykinis drėgmės diapazonas	10 - 90%
--	----------

Logistikos duomenys

Darniosios sistemos (DS) kodas	85176200
--------------------------------	----------

Dokumentai ir vaizdo įrašai

› [Gaminio informacijos lapas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zyxel Networks Corporation

Industry East RD. IX, Hsinchu Science Park 2,
30076 Hsinchu, TW
zyxel.com

ATSAKINGAS ASMUO ES

Zyxel Networks A/S

Adenauerstraße 20/A3, 52146 Würselen, DE
zyxel.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt