

Axagon PCEA-S2N PCIe - 2x serial port 250 kbps adapter w. SP & LP

Gamintojas: **AXAGON** · Modelis: **PCEA-S2N** · EAN: **8595247905406** · Prekės kodas: **654440**



28,89 €

Kaina su PVM

Be PVM: **23,88 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: RS-232
- ✓ 5 Gbit/s
- ✓ Black



Aprašymas

The AXAGON PCEA-S2N PCI-Express card extends your desktop PC by two RS-232 serial ports with DB-9 connectors.

High performance, seamless compatibility and wide port options are ensured by proven ASIX chipset.

Included low profile brackets allow controller installation into standard and also low profile PC cases.

Input:

- PCI-Express 2.0 interface compatible with PCI-Express 1.0a / 1.1 / 2.1 / 3.0.
- Number of lines 1-Lane (x1), compatible with x1 / x4 / x8 / x16 PCIe slots.
- The bandwidth of 1-Lane PCI-Express 2.0 bus 5 Gb/s.

Output:

- 2x serial RS-232 port with DB9 male connectors, the ports are placed on the card's bracket.
- Guaranteed data flow of used RS232 drivers up to 250 kBd.
- Compatible with 16C550 / Extended 16C550 / 16C950 UART.

Other features:

- Plug and Play Support - automatic selection of IRQ and I/O address.
- 256-Byte transmit & receive FIFO buffer for each port.
- Serial port baud rate setting.
- Adjustable word length 5, 6, 7, 8 or 9 bits.
- Adjustable parity (even, odd, none, mark, space), 1, 1.5 or 2 stop bits.
- Adjustable flow control Xon/Xoff, hardware or none.
- The COM port number change.
- Advanced 9-bit data transfer settings and custom baud rate settings.
- Supports TXD, RXD, RTS, CTS, DTR, DCD, DSR, and RI serial signals.
- Serial port electrostatic discharge (ESD) protection exceeding $\pm 15\text{KV}$ Air Gap Discharge and $\pm 8\text{KV}$ Contact Discharge.
- Supports connecting serial devices such as ATMs, cash registers, barcode readers, CNC machines, tablets, modems, POSs or PDAs.
- The ASIX AX99100 chipset is used.

Supported operating systems:

- MS Windows XP / Vista / 7 / 8 / 8.1 / 10 and later, Windows Server 2003 / 2008 / 2012 / 2016 and later (supported all 32 and 64-bit Windows OS versions), with kernel 2.6.11 and above.

Package contains:

- PCI-Express card with a standard bracket,
- low profile brackets,
- multilingual guide CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
- packed in a cardboard box.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	RS-232
Host interface gender	Male
Expansion card form factor	Full-height / Low-profile
Expansion card standard	PCIe 2.0
Serial ports quantity	2
Serial interface type	RS-232
Design	
Internal	Yes
Product colour	Black

Country of origin	China
Certification	CE, RoHS

Features

Data transfer rate (max)	5 Gbit/s
FIFO (First In, First Out)	256 B
Flow control support	Yes
Flow Control type	XON/XOFF
Plug and Play	Yes

System requirements

Windows operating systems supported	Yes
Linux operating systems supported	Yes
Server operating systems supported	Yes

Technical details

Warranty period	2 year(s)
Compliance certificates	RoHS, CE

Packaging data

Quantity per pack	1 pc(s)
Manual	Yes
Package width	110 mm
Package depth	25 mm
Package height	145 mm
Package weight	87 g
Package type	Box