

# LogiLink POE004 PoE adapter Gigabit Ethernet 53 V

Gamintojas: **LOGILINK** · Modelis: **POE004** · EAN: **4052792035223** · Prekės kodas: **654609**



## 42,89 €

Kaina su PVM

Be PVM: **35,45 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Simultaneous transmission of power and data via a network cable
- ✓ Automatic detection of PoE end devices (PD)
- ✓ 2 Gigabit RJ45 ports for faster transmission (10/100/1000BASE-T)
- ✓ Automatic detection and protection of non-standardised Ethernet ports
- ✓ Supports the PoE standards IEEE802.3af and 802.3at
- ✓ Supplies power up to 30 W (PSE), up to 25.5 W at the PD
- ✓ Plug and play - no configuration required
- ✓ 1.5m power cord included



## Aprašymas

### Features:

- Automatically detects PoE terminals and supplies inline power
- Interface: One connector (Data port) for connecting to the passive hub or switch and one connector (Data & power port) for connecting to the PoE PD
- Standard: IEEE802.3 10BASE-T / IEEE802.3u 100BASE-TX / IEEE802.3ab 1000BASE-T / IEEE802.3af
- LED Definition: Power: Green LED (1x), Light off: not connect PD or fail, Light on: connect PD
- AC: Green LED (1x), Light off: power off or fail, Light on: power on

## Techninė specifikacija

### Specifications

Sandėlio grupė Server, Storage & Netzwerk > Switche [+1398][-565]

### Network

Ethernet interface type Gigabit Ethernet

Ethernet LAN data rates 10,100,1000 Mbit/s

Cabling technology 10/100/1000 BASE T(X)

Power over Ethernet (PoE) Yes

Networking standards IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u

### Features

Product colour Black

Rack mounting No

LED indicators Yes

Power protection features Overload, Short circuit

### Ports & interfaces

Ethernet LAN (RJ-45) ports 2

### Power

Power over Ethernet (PoE) voltage 53 V

AC adapter input voltage 100 - 240 V

AC adapter frequency 50/60 Hz

Power over Ethernet (PoE) power per port 30 W

### Certificates

Compliance industry standards RoHS

### Operational conditions

Operating temperature (T-T) 0 - 40 °C

Operating relative humidity (H-H) 10 - 90%

Storage temperature (T-T) -40 - 70 °C

Storage relative humidity (H-H) 5 - 90%

### Weight & dimensions

Dimensions (WxDxH) 58 x 155 x 36 mm

### Packaging content

Number of products included 1 pc(s)

Power cord included Yes

|        |     |
|--------|-----|
| Manual | Yes |
|--------|-----|

**Packaging data**

|               |        |
|---------------|--------|
| Package width | 197 mm |
|---------------|--------|

|                |       |
|----------------|-------|
| Package height | 65 mm |
|----------------|-------|

|                |       |
|----------------|-------|
| Package weight | 464 g |
|----------------|-------|

**Logistics data**

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 85044090 |
|-----------------------------|----------|

|                   |       |
|-------------------|-------|
| Country of origin | China |
|-------------------|-------|