

Microconnect POEINJ-15W PoE adapter 10 Gigabit Ethernet 48 V

Gamintojas: MICRO CONNECT · Modelis: POEINJ-15W · EAN: 5706998614476 · Prekės kodas: 654634



37,90 €

Kaina su PVM

Be PVM: 31,32 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ IEEE802.3af Standard
- ✓ PoE data & power transmission distance 100m
- ✓ Aktive PoE Injector
- ✓ Adaptor Power: 15.4W
- ✓ 100-220V AC, 50-60HZ, 48VDC/0.32A
- ✓ 1.2m EU Power Cord Included



Aprašymas

100-220V, 50-60HZ, 48V DC, Maximum speed rate: 1000Mbps, Transmission distance: 100m

The POEINJ-15W is a single-port Gigabit PoE (Power over Ethernet) device with two RJ45 ports, one port for the Ethernet data input, another port for the integrated data and power supply output. Since the power supply itself does not have the data switch function, it needs to work together with a Network switch. It mixes the data of the network switch with the power supply, and transmits the data and the power supply to the remote powered terminal through the network cable. This can solve the layout restrictions due to the engineering power line. The device can provide PoE power supply to those Ethernet devices conforming to the IEEE802.3af international standard, such as routers, switches, wireless APs, VoIP phones, industrial network terminals, and network cameras etc. It provides efficient engineering solutions for locations where power is not available at the remote end or where the use of Ethernet cable power increase system reliability and simplify equipment installation.

Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Network > Network Adapters [+1948][-605]

Network

Ethernet interface type	10 Gigabit Ethernet
Ethernet LAN data rates	10 Mbit/s
Cabling technology	10/100
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3af
Cable types supported	Cat5

Features

Product colour	Black
Plug and Play	Yes

Ports & interfaces

Ethernet LAN (RJ-45) ports	2
----------------------------	---

Power

Power over Ethernet (PoE) voltage	48 V
Output power	15.4 W
AC adapter input voltage	100 - 240 V
Suitable for use in country/location	Europe

Certificates

Compliance certificates	RoHS
Certification	CE, FCC

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 85%

Weight & dimensions

Width	62 mm
Depth	38.5 mm
Height	165 mm
Weight	250 g

Packaging data

Package width	184 mm
Package depth	139 mm
Package height	57 mm

Package weight	436 g
----------------	-------

Logistics data

Harmonized System (HS) code	85044090
-----------------------------	----------