

Microconnect POEINJ-60W PoE adapter Gigabit Ethernet 55 V

Gamintojas: MICRO CONNECT · Modelis: POEINJ-60W · EAN: 5706998910981 · Prekės kodas: 654635



51,90 €

Kaina su PVM

Be PVM: 42,89 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

✓ Active PoE injector



Aprašymas

The POEINJ-60W is a single-port Gigabit PoE (Power over Ethernet) device with two RJ45 ports, one port for the Ethernet data input, another port for the integrated data and power supply output. Since the power supply itself does not have the data switch function, it needs to work together with a Network switch. It mixes the data of the network switch with the power supply, and transmits the data and the power supply to the remote powered terminal through the network cable. This can solve the layout restrictions due to the engineering power line. The device can provide PoE power supply to those Ethernet devices conforming to the IEEE802.3af/atPoE++ international standard, such as routers, switches, wireless APs, VoIP phones, industrial network terminals, and network cameras etc. It provides efficient engineering solutions for locations where power is not available at the remote end or where the use of Ethernet cable power increase system reliability and simplify equipment installation.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Network

Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	1000 Mbit/s
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3af
Cable types supported	Cat5
Features	
Product colour	Black
Wall mountable	Yes
Easy to install	Yes
Plug and Play	Yes
LED indicators	Yes
Power protection features	Over current
International Protection (IP) code	IP40
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
DC-in jack	Yes
Power	
Power over Ethernet (PoE) voltage	55 V
AC adapter input voltage	100 - 240 V
Power over Ethernet (PoE) power per port	60 W
DC output voltage	55 V
Suitable for use in country/location	Europe
Certificates	
Compliance certificates	RoHS
Certification	CE, FCC, UL
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 70 °C
Weight & dimensions	
Width	65.8 mm
Depth	33.5 mm
Height	145.5 mm
Weight	380 g

Packaging content

Number of products included	1 pc(s)
-----------------------------	---------

Packaging data

Package width	168 mm
---------------	--------

Package depth	141 mm
---------------	--------

Package height	54 mm
----------------	-------

Package weight	456 g
----------------	-------

Logistics data

Harmonized System (HS) code	85044090
-----------------------------	----------

Country of origin	China
-------------------	-------