

LevelOne POI-2012 PoE adapter Fast Ethernet 52 V

Gamintojas: **LEVELONE** · Modelis: **POI-2012** · EAN: **4015867221808** · Prekės kodas: **654639**



34,90 €

Kaina su PVM

Be PVM: **28,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Remove the need for a bulky power adapter and power line
- ✓ Delivers power and data to equipment via a single Ethernet cable
- ✓ Built-in power supply
- ✓ Extends PoE connection for another 100 meters
- ✓ Unique interlocking feature for easy installation



Aprašymas

The LevelOne POI-2012 is a Power over Ethernet injector that not only delivers a cost-effective solution for power distribution, but also provides a seamless way of deployment on the existing LAN infrastructure. With the use of power injectors, DC power of up to 15.4W and the data that comes from a non-PoE switch are merged together and then transmitted to the 802.3af compliant products such as PoE dome cameras through the Ethernet cabling. Hence, preserving your investment in hardware upgrade without the need for buying extra PoE switches. Furthermore, non-PoE devices like wireless access points can also be powered up remotely by adding additional PoE splitters, since power and data are further split into two cables, therefore these devices may be installed in hard-to-reach areas like ceilings where there are no any outlets or electrical wiring nearby.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switches [+1398][-565]

Network

Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3, IEEE 802.3af, IEEE 802.3u

Features

Product colour	Black
Wall mountable	Yes
Plug and Play	Yes
Surge protection	Yes
Maximum operating distance	100 m
LED indicators	PoE, Power
Pin assignment & polarity	4/5 (+), 7/8 (-)

Ports & interfaces

Ethernet LAN (RJ-45) ports	2
----------------------------	---

Power

Power over Ethernet (PoE) voltage	52 V
AC adapter input voltage	100 - 240 V
AC adapter frequency	50/60 Hz
Input current	0.8 A
Output current	0.3 A
Power consumption (max)	15.4 W
Power over Ethernet (PoE) power per port	15.4 W

Certificates

Compliance certificates	RoHS
Certification	FCC Part 15, CE

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	0 - 70 °C
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	143 mm
Depth	51 mm

Height	38 mm
--------	-------

Weight	350 g
--------	-------

Packaging content

Number of products included	1 pc(s)
-----------------------------	---------

Quick installation guide	Yes
--------------------------	-----

Packaging data

Package width	210 mm
---------------	--------

Package depth	125 mm
---------------	--------

Package height	55 mm
----------------	-------

Package weight	400 g
----------------	-------

Package type	Box
--------------	-----

Logistics data

Harmonized System (HS) code	85044095
-----------------------------	----------