

LevelOne Gigabit PoE Injector, 802.3at/af PoE, 30W

Gamintojas: **LEVELONE** · Modelis: **POI-3000** · EAN: **4015867158111** · Prekės kodas: **654640**



83,90 €

Kaina su PVM

Be PVM: **69,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10,100,1000 Mbit/s
- ✓ Black
- ✓ Power over Ethernet (PoE)



Aprašymas

Advanced PoE Solution

The LevelOne POI-3000 is a single port, high power PoE PSE solution for remote PoE PD devices. Generating up to 30W , POI-3000 supplies remote power for new applications such as wireless access points, pan-tilt-zoom (PTZ) IP cameras and videophones. It complies with IEEE 802.3at PoE standard and is backward to IEEE802.3af. It can work with 10/100Base-T networking devices and emerging 1000Base-T devices such as Wi-MAX and wireless IEEE 802.11n access points. For all the function featured in POI-3000, people can get the benefit of flexible network installation at lower cost, less downtime. It also provides a high-bandwidth pipe to the network.

- Up to 30W of PoE Power Feeding on 2-pairs
- IEEE 802.3at Compliant
- IEEE 802.3af backward compatible
- Compatible with IEEE 802.3af or Legacy PoE applications
- Safe on Low Power Devices Receive Only the Power They Need
- Safe and Reliable Power to WLAN Access Points
- Automatic Detection and Protection of Non-standard Ethernet Terminals

- Supports 10/100/1000Base-T LAN environment
- Unique interlocking feature for easy installation

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE)	Yes
Features	
Product colour	Black
LED indicators	PoE, Power
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
Power	
Output power	30 W
AC adapter input voltage	100 - 240 V
AC adapter frequency	50/60 Hz
Input current	0.8 A
Certificates	
Certification	RoHS Compliant, CE/FCC
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	55 mm
Depth	35.5 mm
Height	173.5 mm
Weight	280 g
Packaging content	
Number of products included	1 pc(s)
Packaging data	
Package width	55 mm

Package depth	125 mm
---------------	--------

Package height	210 mm
----------------	--------

Package weight	450 g
----------------	-------

Logistics data

Harmonized System (HS) code	85044095
-----------------------------	----------