

LevelOne Gigabit PoE Injector, 30W

Gamintojas: **LEVELONE** · Modelis: **POI-3004** · EAN: **4015867187821** · Prekės kodas: **654641**



62,90 €

Kaina su PVM

Be PVM: **51,98 €**

Sandėlyje




Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10,100,1000 Mbit/s 100 m
- ✓ Black
- ✓ Power over Ethernet (PoE)



Aprašymas

The LevelOne POI-3004 is a Power over Ethernet (PoE) injector that not only delivers a cost-effective solution for power distribution, but also provides a seamless way of deploying Powered Devices (PDs) on existing LAN infrastructure.

With the use of power injectors, DC power of up to 30W and the data that comes from a non-PoE switch are merged together and then transmitted to a PD such as a PoE network camera, through the Ethernet cabling. This allows you to extend the use of your existing hardware investment without needing to buy extra PoE switches.

Furthermore, non-PoE devices like wireless access points can also be powered up remotely by adding additional PoE splitters, since power and data are further split into two cables. These devices can therefore be installed in hard-to-reach areas like ceilings where there are no outlets or electrical wiring nearby.

- PoE supplies up to 30W of power feeding on 2 pairs
- Remove the need for a bulky power adapter and power line
- Delivers power and data to equipment via a single Ethernet cable

- Remote power feeding up to 100m
- Unique interlocking feature for easy installation
- Surge protected to enhance safety
- Simple Plug and Play installation
- Compact, lightweight design

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE)	Yes
Features	
Product colour	Black
Maximum operating distance	100 m
LED indicators	PoE, Power
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
Power	
Power over Ethernet (PoE) voltage	52 V
Output power	30 W
Input voltage	100 - 240 V
Input frequency	50/60 Hz
Input current	0.8 A
Output current	0.6 A
Power consumption (max)	30 W
Certificates	
Certification	FCC Part 15, CE, RoHS
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	0 - 70 °C
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	

Width	55 mm
Depth	35.5 mm
Height	173.5 mm
Weight	275 g
Packaging content	
Number of products included	1 pc(s)
Power cord included	Yes
Packaging data	
Package width	55 mm
Package depth	125 mm
Package height	210 mm
Package weight	450 g
Logistics data	
Harmonized System (HS) code	85044095