

LevelOne POI-3010 PoE adapter Fast Ethernet, Gigabit Ethernet 52 V

Gamintojas: **LEVELONE** · Modelis: **POI-3010** · EAN: **4015867221815** · Prekės kodas: **654642**



54,90 €

Kaina su PVM

Be PVM: **45,37 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ IEEE 802.3af/at PoE PSE with 30W power budget
- ✓ Unique interlocking feature for easy installation
- ✓ Auto-detection and protection of non-standard PoE devices
- ✓ 10/100/1000Mbps wire speed transmission and reception



Aprašymas

The LevelOne POI-3010 is a single port, high power PoE PSE solution for remote PoE PD devices. Generating up to 30W, the POI-3010 supplies remote power for new applications such as wireless access points, pan-tilt-zoom (PTZ) IP cameras and videophones. It complies with IEEE 802.3at PoE standard and is backward compatible to IEEE802.3af. It can work with 10/100Base-T networking devices and emerging 1000Base-T devices such as Wi-MAX and wireless IEEE 802.11ac access points. For all the function featured in POI-3010, people can get the benefit of flexible network installation at lower cost and less downtime. It also provides a high-bandwidth pipe to the network.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Network

Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u

Features

Product colour	Black
Wall mountable	Yes
Plug and Play	Yes
Surge protection	Yes
Maximum operating distance	100 m
LED indicators	PoE, Power
Pin assignment & polarity	1/2 (+), 3/6 (-)

Ports & interfaces

Ethernet LAN (RJ-45) ports	2
----------------------------	---

Power

Power over Ethernet (PoE) voltage	52 V
AC adapter input voltage	100 - 240 V
AC adapter frequency	50/60 Hz
Input current	0.8 A
Output current	0.6 A
Power consumption (max)	30 W
Power over Ethernet (PoE) power per port	30 W

Certificates

Compliance certificates	RoHS
Certification	FCC Part 15, CE

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	0 - 70 °C
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	143 mm
Depth	51 mm

Height	38 mm
Weight	350 g
Packaging content	
Number of products included	1 pc(s)
Power cord included	Yes
Quick installation guide	Yes
Packaging data	
Package width	210 mm
Package depth	125 mm
Package height	55 mm
Package weight	400 g
Package type	Box
Logistics data	
Harmonized System (HS) code	85044095