

LevelOne POI-3014 PoE adapter Fast Ethernet, Gigabit Ethernet 52 V

 Gamintojas: **LEVELONE** · Modelis: **POI-3014** · EAN: **4015867223185** · Prekės kodas: **654643**


39,91 €

Kaina su PVM

 Be PVM: **32,98 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10,100,1000 Mbit/s 100 m
- ✓ Black
- ✓ Power over Ethernet (PoE) IEEE 802.3, IEEE 802.3ab, IEEE 802.3u



Aprašymas

The LevelOne POI-3014 is a Power over Ethernet (PoE) injector that not only delivers a cost-effective solution for power distribution, but also provides a seamless way of deploying Powered Devices (PDs) on existing LAN infrastructure.

With the use of power injectors, DC power of up to 30W and the data that comes from a non-PoE switch are merged together and then transmitted to a PD such as a PoE network camera, through the Ethernet cabling. This allows you to extend the use of your existing hardware investment without needing to buy extra PoE switches.

Furthermore, non-PoE devices like wireless access points can also be powered up remotely by adding additional PoE splitters, since power and data are further split into two cables. These devices can therefore be installed in hard-to-reach areas like ceilings where there are no outlets or electrical wiring nearby.

Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Netzwerk > Switche [+1398][-565]

Network

Ethernet interface type Fast Ethernet, Gigabit Ethernet

Ethernet LAN data rates 10,100,1000 Mbit/s

Power over Ethernet (PoE) Yes

Networking standards IEEE 802.3, IEEE 802.3ab, IEEE 802.3u

Features

Product colour Black

Wall mountable Yes

Plug and Play Yes

Surge protection Yes

Maximum operating distance 100 m

LED indicators PoE, Power

Pin assignment & polarity 4/5 (+), 7/8 (-)

Ports & interfaces

Ethernet LAN (RJ-45) ports 2

Power

Power over Ethernet (PoE) voltage 52 V

AC adapter input voltage 100 - 240 V

AC adapter frequency 50/60 Hz

Input current 0.8 A

Output current 0.6 A

Power consumption (max) 30 W

Power over Ethernet (PoE) power per port 30 W

Certificates

Compliance certificates RoHS

Certification FCC Part 15, CE

Operational conditions

Operating temperature (T-T) 0 - 45 °C

Operating relative humidity (H-H) 5 - 95%

Storage temperature (T-T) 0 - 70 °C

Storage relative humidity (H-H) 5 - 95%

Weight & dimensions	
Width	145.7 mm
Depth	64.4 mm
Height	43.4 mm
Weight	350 g
Packaging content	
Number of products included	1 pc(s)
Quick installation guide	Yes
Packaging data	
Package width	210 mm
Package depth	145 mm
Package height	55 mm
Package weight	400 g
Logistics data	
Harmonized System (HS) code	85044095