

# LevelOne Gigabit PoE Injector, 60W, 802.3at/af PoE

Gamintojas: **LEVELONE** · Modelis: **POI-5001** · EAN: **4015867199466** · Prekės kodas: **654644**



## 245,90 €

Kaina su PVM

Be PVM: **203,22 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 10,100,1000 Mbit/s
- ✓ Black
- ✓ Power over Ethernet (PoE) IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt



## Aprašymas

POI-5001 is a single port, high-power 60W PoE PSE solution for remote PoE PD devices. Generating up to 60W through 8 pins, POI-5001 supplies remote power for new applications such as wireless access points, pan-tilt-zoom (PTZ) IP cameras, lighting, panel display for digital signage and video-phones. It complies to IEEE 802.3bt PoE++ standards to deliver 60W on both end-point and midspan pairs with a total power of 60W PoE output. It can work with 10/100Base-T networking devices and emerging 1000Base-T devices such as Wi-MAX and wireless IEEE 802.11n access points.

### Key Features

- PoE supplies up to 60W of power feeding on 4 pairs
- Auto-detection and protection of non-standard PoE devices
- IEEE 802.3af/at PoE compliant to simplify deployment and installation

## Techninė specifikacija

## Specifications

Sandėlio grupė Server, Storage & Network > Network Adapters [+1948][-605]

## Network

|                           |                                          |
|---------------------------|------------------------------------------|
| Ethernet interface type   | Gigabit Ethernet                         |
| Ethernet LAN data rates   | 10,100,1000 Mbit/s                       |
| Power over Ethernet (PoE) | Yes                                      |
| Networking standards      | IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt |

## Features

|                |       |
|----------------|-------|
| Product colour | Black |
| LED indicators | Power |

## Ports & interfaces

|                            |   |
|----------------------------|---|
| Ethernet LAN (RJ-45) ports | 2 |
|----------------------------|---|

## Power

|                             |             |
|-----------------------------|-------------|
| Output power                | 60 W        |
| AC adapter input voltage    | 100 - 240 V |
| Input voltage               | 56 V        |
| Power consumption (typical) | 2 W         |

## Certificates

|               |      |
|---------------|------|
| Certification | RoHS |
|---------------|------|

## Operational conditions

|                             |           |
|-----------------------------|-----------|
| Operating temperature (T-T) | 0 - 40 °C |
|-----------------------------|-----------|

## Weight & dimensions

|        |        |
|--------|--------|
| Width  | 180 mm |
| Depth  | 71 mm  |
| Height | 37 mm  |
| Weight | 530 g  |

## Packaging content

|                             |         |
|-----------------------------|---------|
| Number of products included | 1 pc(s) |
| Power cord included         | Yes     |

## Packaging data

|                |        |
|----------------|--------|
| Package width  | 210 mm |
| Package depth  | 125 mm |
| Package height | 60 mm  |
| Package weight | 800 g  |

|                                  |          |
|----------------------------------|----------|
| Package type                     | Box      |
| Logistics data                   |          |
| Harmonized System (HS) code      | 85044095 |
| Master (outer) case width        | 580 mm   |
| Master (outer) case length       | 435 mm   |
| Master (outer) case height       | 277 mm   |
| Master (outer) case gross weight | 33 kg    |
| Products per master (outer) case | 40 pc(s) |
| Country of origin                | Taiwan   |