

# LevelOne Gigabit PoE Repeater, Cascadable

Gamintojas: **LEVELONE** · Modelis: **POR-0120** · EAN: **4015867174920** · Prekės kodas: **654649**



## 200,90 €

Kaina su PVM

Be PVM: **166,03 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Network repeater 100 m 1000 Mbit/s
- ✓ 10/100/1000Base-T(X)
- ✓ Power over Ethernet (PoE)
- ✓ Black



## Aprašymas

For system integrators looking for a professional solution to help extend their PoE network, POR-0120 is the perfect accessory to increase your Power over Ethernet network performance. LevelOne POR-0120, a 1-Port Gigabit PoE Repeater requiring neither configuration nor electrical power, is an innovative transmitter to pass on both data and power extend to another 100 meters. The delivery though one PoE port and one non-PoE port are adequate to extend network devices such as WLAN Access Points, Network Cameras and other appliances with high-speed to the network for greater deployment flexibility.

### PoE Compliance

Our device features PoE (Power-over-Ethernet) capability, which carries electrical power along with data in a safe way using Ethernet cabling. Thus providing great cost savings by eliminating the need for additional power cables and outlets. In addition, it enhances flexibility, for instance, you can set up a PoE wireless access point in close proximity where the reception is better.

### Easy Deployment

No software installation is required. Simply just plug and play as no external power supply is needed, due to all electrical power comes from the PSE (Power Sending Equipment), for instance, it could be a PoE Gigabit Ethernet Switch. Therefore the power source is centrally managed from one

location easily and efficiently.

### Scalable Design

LevelOne network devices are the perfect solution to help you extend your existing PoE network. Normal Ethernet cable, for example the cat5e standard, runs up to 100 meters, but with the installation of a single PoE repeater can increase the distance up to 200 meters. Furthermore, you can triple your range or even more by daisy-chaining multiple PoE repeaters.

## Techninė specifikacija

| Specifications                           |                                                            |
|------------------------------------------|------------------------------------------------------------|
| Sandėlio grupė                           | Server, Storage & Network > Network Adapters [+1948][-605] |
| Performance                              |                                                            |
| Type                                     | Network repeater                                           |
| Maximum transfer distance                | 100 m                                                      |
| Data transfer rate                       | 1000 Mbit/s                                                |
| Auto MDIX IEEE                           | Yes                                                        |
| Duplex system                            | Full, Half                                                 |
| Network                                  |                                                            |
| Cabling technology                       | 10/100/1000Base-T(X)                                       |
| Networking standards                     | IEEE 802.3af, IEEE 802.3x                                  |
| Ports & interfaces                       |                                                            |
| Ethernet LAN (RJ-45) ports               | 2                                                          |
| Power over Ethernet (PoE) ports quantity | 2                                                          |
| Design                                   |                                                            |
| Product colour                           | Black                                                      |
| LED indicators                           | PoE, Power                                                 |
| Country of origin                        | Taiwan                                                     |
| Certification                            | FCC Rules Part 15, CE                                      |
| Power                                    |                                                            |
| Power consumption (max)                  | 2.5 W                                                      |
| Power over Ethernet (PoE)                | Yes                                                        |
| Operational conditions                   |                                                            |
| Operating temperature (T-T)              | 0 - 50 °C                                                  |
| Storage temperature (T-T)                | -20 - 90 °C                                                |
| Operating relative humidity (H-H)        | 5 - 95%                                                    |
| Weight & dimensions                      |                                                            |

|                             |          |
|-----------------------------|----------|
| Width                       | 90 mm    |
| Depth                       | 120 mm   |
| Height                      | 28 mm    |
| Weight                      | 400 g    |
| Packaging data              |          |
| Package width               | 148 mm   |
| Package depth               | 235 mm   |
| Package height              | 80 mm    |
| Package weight              | 530 g    |
| Logistics data              |          |
| Harmonized System (HS) code | 85176990 |