

LevelOne Gigabit IEEE802.3bt PoE Splitter

Gamintojas: **LEVELONE** · Modelis: **POS-5000** · EAN: **4015867231111** · Prekės kodas: **654656**



95,90 €

Kaina su PVM

Be PVM: **79,26 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Auto-detection and protection of non-standard PoE devices
- ✓ 10/100/1000Mbps wire speed transmission and reception
- ✓ Automatically detects PoE terminals and supplies inline power
- ✓ Intergrates Non-PoE devices with Power Over Ethernet support
- ✓ Safeguards network device with short circuit protection
- ✓ Reduce installation and network equipment costs
- ✓ Adjustable DIP switch for 12V, or 24V output
- ✓ Compact splitter supports Gigabit speeds
- ✓ Supplies power up to 60 watts
- ✓ Provides Interchangeable tips



Aprašymas

The LevelOne POS-5000 Gigabit High Power PoE Splitter splits a networked PoE signal into separated power and Gigabit data sources. This device allows administrators to run Gigabit speed PoE cables over long distances and then split the PoE signal into separated data and power sources in order to network non-PoE devices. Active splitters are also available in the following output voltages (12V or 24V). Save installation and equipment cost when installing WiFi access points, (Pan/Tilt/Zoom) IP cameras and more in remote locations. No need to install network devices near a power outlet. This compact device safeguards valuable network equipment with short circuit protection and quickly creates an integrated PoE and non PoE network at Gigabit speeds.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Features	
Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
Cabling technology	10/100/1000Base-T(X)
Power over Ethernet (PoE)	Yes
Product colour	Black
LED indicators	Yes
Ports & interfaces	
RJ-45 input ports	1
RJ-45 output ports	1
DC-out jack	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	53 mm
Depth	24 mm
Height	80 mm
Weight	80 g
Packaging content	
Cables included	DC, LAN (RJ-45)
Packaging data	
Package width	125 mm
Package depth	55 mm
Package height	125 mm
Package weight	600 g
Power	
DC output voltage	12V, 24V
Output power	60 W
Logistics data	
Pallet gross length	80 cm
Pallet gross width	120 cm

Pallet gross height	168 cm
Country of origin	China
Master (outer) case width	290 mm
Master (outer) case length	270 mm
Master (outer) case height	640 mm
Master (outer) case gross weight	5.5 kg
Products per master (outer) case	50 pc(s)