

LevelOne Gigabit PoE bt to USB-C PD 3.0 Splitter

Gamintojas: **LEVELONE** · Modelis: **POS-5001** · EAN: **4015867231128** · Prekės kodas: **654657**



108,90 €

Kaina su PVM

Be PVM: **90,00 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with IEEE802.3af, IEEE802.3at, IEEE802.3bt.
- ✓ Data speed 10/100/1000Mbps
- ✓ Auto-Sensing Algorithm enables taking power from PSE.
- ✓ Splits the Data and Power from PoE to Type-C devices.
- ✓ Wide input voltage range 36Vdc to 57Vdc.
- ✓ Maximum power output up to 50W.
- ✓ Output PD3.0 Fast charge DC5V/3A, 9VDC/3A, 12VDC/3A, 15V3A, 20V2.25A.
- ✓ Thermal cut off.
- ✓ Over voltage protection (OVP)
- ✓ Over current protection (OCP).



Aprašymas

The LevelOne POS-5001 Gigabit High Power PoE Splitter splits a networked PoE Signal into separated power and Gigabit data sources. This device allows administrators to run Gigabit speed PoE cables over long distances and then split the PoE signal into separated data and power sources in order to network non-PoE devices. Active splitters are also available in the following output voltages (5V~24V) USB Type-C.

Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

Features

Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
Cabling technology	10/100/1000Base-T(X)
Power over Ethernet (PoE)	Yes
Product colour	Black
LED indicators	Activity, Link, Power

Ports & interfaces

RJ-45 input ports	1
RJ-45 output ports	1
USB Type-C output ports	1

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	0 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Certificates

Compliance certificates	CE, RoHS, UKCA
-------------------------	----------------

Weight & dimensions

Width	53 mm
Depth	24 mm
Height	80 mm
Weight	85 g

Packaging data

Package width	125 mm
Package depth	55 mm
Package height	125 mm
Package weight	900 g

Power

DC output voltage	5V, 12V, 24V
Output power	50 W
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3

Logistics data

Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet gross height	170 cm
Country of origin	China
Master (outer) case width	290 mm
Master (outer) case length	270 mm
Master (outer) case height	640 mm
Master (outer) case gross weight	5 kg
Products per master (outer) case	50 pc(s)
Sustainability	
Sustainability compliance	Yes