

# TP-Link PSM900-AC power supply unit 900 W Metallic

Gamintojas: **TP-LINK** · Modelis: **PSM900-AC** · EAN: **4895252502718** · Prekės kodas: **654727**



## 870,90 €

Kaina su PVM

Be PVM: **719,75 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Hot swappable
- ✓ Output over-voltage/under-voltage/short circuit/over-current protection
- ✓ Applicable to multiple TP-Link Omada and TP-Link Omada Pro switch models



## Aprašymas

The TP-Link Power Supply Module PSM900-AC is an AC-input and DC-output power supply module. It can convert the input voltage to 53.5 Volts with a maximum output power of 900 Watts. The power supply module is fully hot-swappable, helping to ensure no system interruption during installation or replacement. The TP-Link Power Supply Module is applicable to multiple TP-Link Omada and TP-Link Omada Pro switch models, such as SG6428XHP, SG6654XHP, S6500-24GP4XF, 6500-48GP6XF, S6500-24MPP4Y, and S6500-48MPP6Y.

## Techninė specifikacija

### Specifications

Sandėlio grupė

Server, Storage & Network > Network Adapters [+1948][-605]

### Power

|                                   |                                                                                  |
|-----------------------------------|----------------------------------------------------------------------------------|
| Total power                       | 900 W                                                                            |
| AC input voltage                  | 100 - 240 V                                                                      |
| AC input frequency                | 50/60 Hz                                                                         |
| Maximum input current (@110V)     | 12 A                                                                             |
| Maximum input current (@220V)     | 10 A                                                                             |
| Power protection features         | Over current, Over voltage, Short circuit, Under voltage                         |
| <b>Performance</b>                |                                                                                  |
| Compatible products               | SG6428XHP, SG6654XHP, S6500-24GP4XF, S6500-48GP6XF, S6500-24MPP4Y, S6500-48MPP6Y |
| <b>Design</b>                     |                                                                                  |
| Product colour                    | Metallic                                                                         |
| LED indicators                    | Yes                                                                              |
| <b>Operational conditions</b>     |                                                                                  |
| Operating temperature (T-T)       | 0 - 45 °C                                                                        |
| Storage temperature (T-T)         | -40 - 70 °C                                                                      |
| Operating relative humidity (H-H) | 10 - 90%                                                                         |
| Storage relative humidity (H-H)   | 5 - 90%                                                                          |
| <b>Weight &amp; dimensions</b>    |                                                                                  |
| Width                             | 95.8 mm                                                                          |
| Depth                             | 259.5 mm                                                                         |
| Height                            | 40.1 mm                                                                          |
| <b>Logistics data</b>             |                                                                                  |
| Quantity per pack                 | 1 pc(s)                                                                          |
| <b>Other features</b>             |                                                                                  |
| Mounting type                     | Rack mounting                                                                    |