

TP-Link RE900XD network extender Network transmitter White 10, 100, 1000, 2500 Mbit/s

 Gamintojas: **TP-LINK** · Modelis: **RE900XD** · EAN: **4897098688311** · Prekės kodas: **654976**


189,90 €

Kaina su PVM

 Be PVM: **156,94 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ AX6000 Dual Band Wi-Fi – Boosts overall speeds up to an incredible 6000 Mbps with 8x Wi-Fi streams
- ✓ 160 MHz Channel Bandwidth – Expands bandwidth to double the network speed of traditional 80 MHz
- ✓ Full Gigabit Ethernet Ports – High-speed wired connections for an ultra-reliable network
- ✓ Seamless Roaming – Walk from room to room and stay connected with the fastest possible speeds
- ✓ Improved Capacity, Less Lag – Experience flawless streams on more screens throughout your home
- ✓ Simple Installation – Easy setup with the Tether app



Aprašymas

Doubled Channel Speeds with HE160

Supports 4x4 160 MHz on the 5G band for wider bandwidth and faster speeds than the traditional 80 MHz. This ensures higher efficiency and lower latency home networking.

The Simplest Whole-Home EasyMesh

EasyMesh™ works across different access points to create seamless Wi-Fi. Experience strong, stable connections throughout your home. There's no

need to replace your existing EasyMesh™ and OneMesh™ devices with TP-Link's EasyMesh.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server/Storage/Network > Access Points/Routers [+1151][-307]
Performance	
Type	Network transmitter
Ethernet LAN data rates	10,100,1000,2500 Mbit/s
WPS push button	Yes
Windows operating systems supported	Yes
Mac compatibility	Yes
Linux operating systems supported	Yes
Browser supported	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Antenna	
Antenna type	Internal
Network	
Cabling technology	10/100/1000Base-T(X)
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Security algorithms	WPA, WPA2-PSK, WPA3, WPS
Design	
Product colour	White
LED indicators	Yes
Reset button	Yes
Power	
AC input voltage	100 - 240 V
AC input frequency	50 / 60 Hz
Power consumption (typical)	9.2 W
Power consumption (max)	18 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating temperature (transmitter)	10 - 90 °C
Storage temperature (transmitter)	5 - 90 °C

Weight & dimensions

Width	189 mm
Depth	59 mm
Height	200 mm

Packaging content

Quick start guide	Yes
-------------------	-----

Certificates

Compliance certificates	Federal Communications Commission (FCC), RoHS
-------------------------	---

Sustainability

Sustainability compliance	Yes
---------------------------	-----