

Zebra RS5100 Wearable bar code reader 1D/2D LED Black

Gamintojas: **ZEBRA** · Modelis: **RS51C0-LBSNWR** · EAN: **8596375210042** · Prekės kodas: **655029**



1 011,90 €

Kaina su PVM

Be PVM: **836,28 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wearable bar code reader Black
- ✓ Scanner type: 1D/2D Sensor type: LED
- ✓ Code 11, Code 128, Code 39, Code 93, GS1 DataBar, MSI, UPC-A, UPC-E Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
- ✓ 1280 x 960 pixels
- ✓ Tilt reading angle: -60 - 60°
- ✓ Wireless Standard interfaces: Bluetooth
- ✓ Bluetooth Low Energy (BLE) Near Field Communication (NFC)
- ✓ Power source type: Battery Lithium-Ion (Li-Ion) 480 mAh



Aprašymas

THE 'GO-EVERYWHERE' FEATHERWEIGHT AND RUGGED RING SCANNER

Finally, there's a ring scanner that's designed for use in customer-facing areas, as well as your warehouse and distribution center — the RS5100 next-generation ring scanner. It's practically weightless, and so small your customers won't even notice it. There's a wearing option that will bring comfort to every worker. Best-in-class scanning enables instant capture of virtually every barcode at twice the range of legacy Bluetooth ring scanners. The rugged design outshines competitive devices. And a long list of features provides unsurpassed versatility and flexibility.

SUPERIOR ERGONOMICS FOR SUPERIOR COMFORT

At just over two ounces and two cubic inches, it's practically weightless (about 1/2 the size and weight of the legacy RS507x ring scanner). Wear it on a finger, the back of a hand or on a lanyard. The single-sided trigger model accommodates gloves; the double trigger model lets workers switch

hands on the fly. And the top-mounted trigger on both models allows rotation of the RS5100 to the side of a finger for near-zero protrusion.

INDUSTRY-LEADING RUGGED DESIGN

You get a best-in-class rugged design with a drop, tumble and IP sealing specification — so you can count on reliable operation despite drops, bumps, dust and even a high-pressure hose down. The long-life trigger handles millions of actuations. And the RS5100 is built to handle the high levels of electrostatic discharge common with use on concrete flooring.

BEST-IN-CLASS SCANNING

Two scan engine options allow you to choose the imager that best matches your scanning and aimer requirements — LED or laser. Both imager engines deliver first time capture of even damaged, dirty and poorly printed 1D/2D barcodes through PRZM Intelligent Imaging, a megapixel sensor and superior algorithms — plus a wide field of view for easy capture of large barcodes. In addition, the two imagers can scan barcodes twice the distance as the legacy RS507x ring scanner.

Techninė specifikacija

Specifications	
Sandėlio grupė	Sonstiges > Barcode Scanner [+994][-201]
Scanning	
Type	Wearable bar code reader
Scanner type	1D/2D
Sensor type	LED
Linear (1D) barcodes supported	Code 11, Code 128, Code 39, Code 93, GS1 DataBar, MSI, UPC-A, UPC-E
2D (matrix & stacked) barcodes supported	Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
Optical sensor resolution (W x H)	1280 x 960 pixels
Light levels (direct sunlight)	0 - 107639 lx
Wavelength	610 nm
Tilt reading angle	-60 - 60°
Pitch reading angle	-60 - 60°
Yaw reading angle	0 - 360°
Ports & interfaces	
Connectivity technology	Wireless
Standard interfaces	Bluetooth
Bluetooth version	4
Bluetooth Low Energy (BLE)	Yes
Near Field Communication (NFC)	Yes
Performance	
Product colour	Black
LED indicators	Yes

Power	
Power source type	Battery
Battery technology	Lithium-Ion (Li-Ion)
Battery type	Built-in battery
Battery capacity	480 mAh
Weight & dimensions	
Weight	70 g
Width	28 mm
Depth	21 mm
Height	61 mm
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	5 - 95%
Logistics data	
Harmonized System (HS) code	84716070