

Yealink SIP-T48U IP telefonas Pilka LED „Wi-Fi“

Gamintojas: **YEALINK** · Modelis: **SIP-T48U** · EAN: **6938818304321** · Prekės kodas: **656704**



273,90 €

Kaina su PVM

Be PVM: **226,36 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt



Aprašymas

Easy Customization and High Expansibility

The SIP-T48U has a seven-inch, 800 x 480-pixel, backlit- color touch screen, which enables a rich visual presentation and easy navigation. Accompanied by two USB ports, the T48U is your right-hand man in the office that makes Bluetooth, Wi-Fi, USB headset and USB recording possible, and you can use any two of them freely according to your needs to enrich phone features. Meanwhile, the phone not only has 29 one-touch DSS keys that can be easily programmed to various features, but also can connect up to three expansion modules, for up to 180 additional buttons with a screen-based LCD display and LED system.

HD Audio

Yealink Optima HD Voice technology combines cutting-edge hardware and software with wideband technology for maximum acoustic performance. Being a totally open, highly versatile audio codec, Opus, is designed to perform a higher HD audio quality than other wideband codecs in a high network bandwidth; However, if your current network quality is poor, Opus can provide you with a better audio quality than other narrowband codecs. And its hearing aid compatible (HAC) handset helps the person who is with hearing loss to hear the voice more clearly.

Efficient Installation and Provisioning

Yealink T4U series supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings, which makes the T4U series simple to deploy, easy to maintain and upgrade. Furthermore, a unified firmware and auto-p template that applies to all T4U phone models (T41U, T43U, T46U and T48U), saves even more time and costs for businesses, as well as simplifies the management and maintenance.

Secure Transport and Interoperability

The SIP-T48U uses SIP over Transport Layer Security (TLS/SSL), which is the latest network security technology. It's also compatible with leading soft switch suppliers, such as 3CX, Broadsoft Broadworks.

Techninė specifikacija

Konstrukcija	
Gaminio tipas	IP telefonas
Produkto spalva	Pilka
Telefono ragelio tipas	Laidinis telefonas
Telefono funkcijos	
Skambintojo ID	Taip
Telefonų knygėlės talpa	1000 įrašai
VoIP paskyrų skaičius	16
Skambučio laukimas	Taip
Skambučio užlaikymas	Taip
Skambučių peradresavimas	Taip
Konferencinio skambučio galimybė	Taip
Perrinkimas	Taip
Valdymo funkcijos	
Klaviatūros mygtukų skaičius	29
Ekranas	
Lietimui jautrus ekranas	Taip
Ekranas	LED
Ekranų įstrižainė	17,8 cm (7")
Ekranų rezoliucija	800 x 480 pikseliai
Apšviestas ekranas	Taip
Garsas	

Garsiakalbis	Taip
Balso kodekai	AGC, AJB, AMR-WB, CNG, G.711, G.722, G.723.1, G.726, G.729ab, VAD, iLBC
Tinklas	
Ethernet LAN jungtis	Taip
„Wi-Fi“	Taip
Bluetooth	Taip
Eterneto LAN sąsajos tipas	Gigabitinis eternetas
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Apsaugos algoritmų palaikymas	AES, HTTPS, SRTP, TLS
Ryšys	
USB 2.0 portų kiekis	2
Ethernet LAN (RJ-45) portų kiekis	2
Plėtros modulio palaikymas	Taip
Energijos valdymas	
Maitinimas per Eternetą (PoE)	Taip
AC adapterio įėjimo įtampa	100 - 240 V
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Darbo santykinės drėgmės diapazonas	10 - 95%
Svoris ir matmenys	
Plotis	226 mm
Ilgis	226 mm
Aukštis	185 mm
Pakuotės turinys	
Pridėtų rankenų skaičius	1 vnt
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85171800

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

Yealink Network Technology Co., Ltd

Hu'an Road High Tech Park 666, Huli District Xiamen, CN

yealink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt