

iiyama TF3239AS-B1AG kompiuterio monitorius 80 cm (31.5") 1920 x 1080 pikseliai „Full HD“ LED Lietimui jautrus ekranas Juoda

Gamintojas: **IIYAMA** · Modelis: **TF3239AS-B1AG** · EAN: **4948570123865** · Prekės kodas: **657088**



1 128,91 €

Kaina su PVM

Be PVM: **932,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 80 cm (31.5") Juoda
- ✓ Įmontuoti garsiakalbiai
- ✓ HDMI versija: 2.0 „DisplayPort“ kiekis: 1 „DisplayPort“ versija: 1.2
- ✓ Ekrano forma: Plokščias
- ✓ Maksimalus atnaujinimo dažnis: 60 Hz Reakcijos laikas: 8 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1920 x 1080 pikseliai „Full HD“ Skydo tipas: IPS
- ✓ Energijos vartojimo efektyvumo klasė (SDR): F ErP CB, CE, cTUVus, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE





Aprašymas

Enjoy an all-in-one interactive display that combines the best in PCAP Touchscreen technology, offering the versatility and freedom of Android OS, easily customized to your needs by installing applications directly to it. Offering a powerful, yet flexible user experience, fostering creative communication with the benefits of a secure and controllable Touchscreen. The refined edge-to-edge glass design of the TF3239AS-B1AG lends itself for integration into a large variety of environments where polished design and functionality are needed, like Huddle spaces in the modern office space, Retail shops and Kiosks. The on-board iiSignage2 CMS (Content Management System) gives you total control of your messaging and advertising, remotely and safely. The EShare App enables you to bring effortless ideation and efficient collaboration in your enterprise or school. You can start sharing wireless easier than ever before; while the FailOver feature ensures your content is always actively displayed through your choice of inputs For ease of integration, the TF3239AS-B1AG can be equipped with optional external mounting brackets (OMK4-4).

Techninė specifikacija

Display	
Display diagonal	80 cm (31.5")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	1200:1
Maximum refresh rate	60 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	40
Display brightness (typical)	500 cd/m²
Display brightness	435 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt


Anti-glare screen	Yes
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.363 x 0.363 mm
Horizontal scan range	28 - 160 kHz
Viewable size, horizontal	69.8 cm
Viewable size, vertical	39.3 cm
Display diagonal (metric)	80 cm
Haze rate	25%
Surface hardness	7H
Colour depth	8 bit
Performance	
Operating hours (hours/days)	24/7
Operating system installed	Android 11
Operating system version	11
Palm rejection	Yes
Multimedia	
Built-in speaker(s)	Yes
Number of speakers	2
RMS rated power	20 W
Design	
Product colour	Black
Front bezel colour	Black
Glass thickness	3 mm
Ports & interfaces	
USB 2.0 Type-A ports quantity	2
USB Touch port	Yes
DVI port	No
HDMI ports quantity	2
HDMI version	2
DisplayPorts quantity	1
DisplayPort version	1.2
HDCP	Yes
HDCP version	2.2

RS-232C	Yes
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	200 x 200 mm
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Czech, Danish, German, English, Spanish, Finnish, French, Italian, Norwegian, Dutch, Polish, Russian, Swedish
Number of OSD languages	13
Power	
Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	31.3 kWh
Power consumption (typical)	50 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width (with stand)	746.2 mm
Depth (with stand)	62.4 mm
Height (with stand)	440.7 mm
Weight (with stand)	13.2 kg
Bezel width (side)	2.2 cm
Bezel width (top)	2.2 cm
Bezel width (bottom)	2.2 cm
Packaging data	
Package width	840 mm
Package depth	149 mm

Package height	560 mm
Package weight	16.6 kg
USB cable length	1.8 m
Packaging content	
Cables included	AC, USB, HDMI
Remote control included	Yes
Quick start guide	Yes
HDMI cable length	1.8 m
Power cable length	1.8 m
Batteries included	Yes
Remote control batteries included	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP65
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Positional accuracy	2.5 mm
Placement supported	Indoor
Brightness	435 cd/m²
Built-in processor	Yes
Active display area (W x H)	698.4 x 392.8 mm
USB ports quantity	2
Weight	13.2 kg
Height	440.7 mm
Width	746.2 mm
Depth	62.4 mm
Compliance certificates	CB, CE, cTUVus, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
Mean time between failures (MTBF)	50000 h
Ethernet LAN (RJ-45) ports	1
Package volume	16600 cm³
Certification	TCO Certified, CB, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH

User controls	picture (brightness, contrast, sharpness, back level, tint, colour, noise reduction, gamma selection, low blue light, colour temp., colour control, overscan, picture reset), screen (zoom mode, custom zoom, screen reset), audio (balance, treble, bass, volume, audio out (line out), max. volume, min. volume, mute, audio reset, audio out sync, speaker setting), configuration 1 (Android launcher, switch on state, Touch lock, Touch mode, mouse mode, panel saving, RS232 routing, boot on source, WOL, conf.1 reset, factory reset), configuration 2 (OSD timeout, OSD H position, OSD V position, system rotation, info OSD, logo and animation, logo setting, animation setting, monitor ID, monitor info, HDMI version, conf. 2 reset), advanced options (kiosk mode, side bar, no signal image, motorized stand, IR control, power LED light, fan, off timer, schedule, HDMI with one wire, HDMI with one wire off, failover, language, OSD transparency, power saving, advanced options reset)
Touch method	stylus, finger, glove (latex)
Control panel	Power
Thin Client	
Processor architecture	ARM Cortex-A73
Technical details	
Native refresh rate	60 Hz
Matmenys ir svoris	
Matmenys (I × P × A)	84,00cm × 56,00cm × 15,00cm

Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė **F** A-G

- > [Energijos etiketė](#)
- > [Gaminio informacijos lapas](#)
- > [EPREL duomenų bazė](#)



1000/1000

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas
- › Vaizdo įrašas 1 [objects.icecat.biz/objects/122341215_67161138.mp4](objects.icecat.biz/objects/122341215_67161138.mp4)
- › Vaizdo įrašas 2 [objects.icecat.biz/objects/122341215_67161130.mp4](objects.icecat.biz/objects/122341215_67161130.mp4)
- › Vaizdo įrašas 3 [objects.icecat.biz/objects/122341215_67161135.mp4](objects.icecat.biz/objects/122341215_67161135.mp4)
- › Vaizdo įrašas 4 [objects.icecat.biz/objects/122341215_67161131.mp4](objects.icecat.biz/objects/122341215_67161131.mp4)
- › Vaizdo įrašas 5 [objects.icecat.biz/objects/122341215_67161150.mp4](objects.icecat.biz/objects/122341215_67161150.mp4)
- › Vaizdo įrašas 6 [objects.icecat.biz/objects/122341215_67161145.mp4](objects.icecat.biz/objects/122341215_67161145.mp4)
- › Vaizdo įrašas 7 [youtube.com/watch?v=8Qnh8R_KSUC](youtube.com/watch?v=8Qnh8R_KSUC)

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL
iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt