

TP-Link 8-Port 10/100Mbps + 3-Port Gigabit Desktop Switch with 8-Port PoE+

Gamintojas: **TP-LINK** · Modelis: **TL-SL1311P** · EAN: **4895252500295** · Prekės kodas: **657211**



94,90 €

Kaina su PVM

Be PVM: **78,43 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8x 10/100 Mbps RJ45 Ports, 2x Gigabit RJ45 Ports, 1x Gigabit SFP Port
- ✓ 8x PoE+ ports transfer data and power on individual cables
- ✓ Works with IEEE 802.3af/at compliant PDs
- ✓ Supports PoE Power up to 30 W for each PoE port
- ✓ Supports PoE Power up to 65 W for 8 PoE ports*
- ✓ Up to 250 m data and power transmitting range under Extend Mode**
- ✓ Isolation Mode allows one-click client traffic separation for higher security and performance
- ✓ PoE Auto Recovery guarantees stable operation of PoE devices by automatically rebooting the dropped or unresponsive PD devices
- ✓ Fanless Design reduces power consumption and works silently in its location
- ✓ Plug and play with no configuration required



Techninė specifikacija

Specifications

Sandėlio grupė

Server, Storage & Netzwerk > Switches [+1398][-565]

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0

Network

Networking standards	IEEE 802.3af, IEEE 802.3at
10G support	No

Data transmission

MAC address table	2000 entries
Switching capacity	7.6 Gbit/s
Forwarding rate	5.6544 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	16

Design

Rack mounting	No
Product colour	Black
Reset button	Yes
LED indicators	Yes

Power

Power source	AC/DC
Power supply included	Yes
DC input voltage	53.5 V
Power consumption (max)	77.32 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Total Power over Ethernet (PoE) budget	65 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	209 mm
-------	--------

Depth	126 mm
-------	--------

Height	26 mm
--------	-------

Packaging content

Cables included	LAN (RJ-45)
-----------------	-------------

Packaging data

Package type	Box
--------------	-----

Certificates

Certification	FCC, CE, RoHS
---------------	---------------