

ATEN 2-Port 4K DisplayPort USB-C KVM Dock Switch with Power Pass-through

Gamintojas: **ATEN** · Modelis: **US3311** · EAN: **4710469342806** · Prekės kodas: **657656**



188,91 €

Kaina su PVM

Be PVM: **156,12 €**

Sandėlyje





Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2-in-1 solution for 2 USB-C host devices – combines a KVM switch and a multiport dock with 4 x USB 3.2 Gen 1 Type-A ports, 1 x DisplayPort, 1 x USB-C PD input, and 1 x DC jack input
- ✓ Superior video quality – up to True 4K (3840 X 2160 @ 60 Hz)
- ✓ ATEN Video DynaSync™ Technology - eliminates boot-up display problems and optimizes resolutions when switching among video sources
- ✓ USB 3.2 Gen 1 compliant
- ✓ Up to 5 Gbps data transfer rates
- ✓ Supports DP 1.4 Alt Mode
- ✓ Supports PD 3.0 up to 100 W USB PD charging – allows your laptop to obtain the maximum power via your USB-C power adapter
- ✓ Host device selection via the included port switch button
- ✓ Plug-and-Play – no drivers needed



Aprašymas

Switch Between 2 USB-C Laptops

US3311 takes our agile and powerful KVM switch solutions to another dimension. It enables plug-n-play single USB-C cable connection so that 2 laptops can share 1 monitor and 1 keyboard and mouse set, plus 4K@60 and 4-port USB 3.2 SuperSpeed connectivity significantly save desk space and boost your efficiency.

Superb 4-Port SuperSpeed Expansion

With 4 USB 3.2 gen1 ports, transfer data at up to 5Gb/s. Charge and power external devices, no need for an extra USB hub.

Unreal Switching Speed

Exclusive ATEN technology brings astoundingly fast switching speed. Switching between two systems takes three seconds,* making your workflow more efficient than ever before.

Always Correct Resolutions and Display Configurations

ATEN's patented Video DynaSync™ ensures correct resolutions and display configurations when switching ports under all operating systems, ensuring smooth desktop operation.

Exceptional AV Performance in Vivid 4K@60Hz

US3311 empowers your desktop operations with visual enhancement thanks to 4K DCI compliance. It supports up to 3840x2160@60Hz and also works with 21:9 Ultrawide and 32:9 super Ultrawide monitors for graphics-intensive work.

Work While Charging with 100W Power Delivery

The USB-C KVM dock switch also works as a charging station to keep your USB-C devices and USB peripherals powered on.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switche [+1398][-565]
Ports & interfaces	
Number of computers controlled	2
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
DisplayPorts quantity	1
USB hub	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	4
USB Type-C ports quantity	3
DC-in jack	Yes
Performance	
HD type	4K Ultra HD
Maximum resolution	3840 x 2160 pixels
Video bandwidth	60 Hz
Data transfer rate (max)	5 Gbit/s
Plug and Play	Yes
Design	
Product colour	Silver
Housing material	Aluminium

Wired remote switch	Yes
LED indicators	Yes
Display	
Built-in display	No
Power	
Power source	DC
Input voltage	12 V
Input current	3 A
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	100 W
System requirements	
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64
Mac operating systems supported	Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Other operating systems supported	Android
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	119 mm
Depth	143 mm
Height	23.8 mm
Weight	350 g
Packaging data	
Package width	62 mm
Package depth	283 mm
Package height	173 mm
Package volume	1982.18 cm³
Package weight	1.01 kg

Packaging content

Cables included	USB Type-C
Manual	Yes
AC adapter included	Yes
Remote control included	Yes

Logistics data

Master (outer) case net weight	4.25 kg
Master (outer) case width	300 mm
Master (outer) case length	336 mm
Master (outer) case height	194 mm
Master (outer) case gross weight	5.43 kg
Master (outer) case volume	19538.62 cm ³
Country of origin	Taiwan