

## Zyxel USGFLEX50HP-EU0102F hardware firewall 0.35 Gbit/s

Gamintojas: **ZYXEL** · Modelis: **USGFLEX50HP-EU0102F** · EAN: **4718937638307** · Prekės kodas: **657807**



### 590,90 €

Kaina su PVM

Be PVM: **488,35 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

### Pagrindinės savybės

- ✓ Deliver up to 350 Mbps firewall throughput and 90 Mbps VPN throughput
- ✓ 10 concurrent Ipsec VPN connections with SHA-2 encryption
- ✓ High Throughput Gb Ports, 1x WAN, 4x LAN/DMZ
- ✓ Optional security license pack service includes content filter
- ✓ Flexible to adapt to on-premises or Nebula cloud
- ✓ Strong VPN reliability and security for your business
- ✓ Manage all distributed networks from one single screen
- ✓ Web Filtering protects you from undesirable content
- ✓ Device Insight reduces the cyber attack surface
- ✓ Analytics report and enhanced insights



### Aprašymas

#### Nebula Together

The USG FLEX 50 is now part of the Nebula cloud management family with the same easy management interface and streamlined configuration & updates. The network functions and management services are pushed to the cloud and are optimized for managing distributed networks. The USG FLEX 50 helps customers to comply with regulations by offering log archiving service without the need for additional hardware and software installation.

#### Robust VPN Connections

The USG FLEX 50 provides comprehensive VPN connection types including IKEv2, SSL & IPsec VPN. All offer customers secured remote connections. IPsec VPN hardware engine for high-efficiency VPN tunnel. VPN load balance/failover with IKEv2 ensures strong VPN reliability and security for your

business.

### Comprehensive Content Filter Service

The USG FLEX 50 delivers enhanced content filtering functionality and security through its powerful combination of both reputation and category-based filtering. A newly added DNS content filter offers a better approach to inspect web access, particularly when the website is deploying ESNI (Encrypted Server Name Indication) where the traditional URL filtering is not applicable to the destination domain.

### Device Insight

Device Insights give you more visibility of your networks including wired, wireless, BYOD, and IoT devices. You can create access policy with device contextual such as OS version or device category to enforce network segmentation. This reduces the attack surface and prevents threats from spreading. This also helps SMB(s) reduce time spent on investigation.

### Analytics Report and Enhanced Insights

SecuReporter premium offers comprehensive protection and analytics. Utilize SecuReporter premium for a suite of advanced analysis and reporting tools including Sandboxing, Threat Website Analytics, and Threat IP Analytics. Users can also run customized report on-demand or on a regular schedule such as daily, weekly, and monthly.

### Optional Security Pack

The USG FLEX 50 provides an indispensable feature set to perfectly fit small business requirements as well as to gain essential security services needed, including Web Filtering, SecuReporter Premium, and Security Profile Sync, to protect against cyberattacks. In addition, Nebula Control Center (NCC) also offers multiple subscription options to meet customers' needs.

## Techninė specifikacija

| Specifications                           |                                                    |
|------------------------------------------|----------------------------------------------------|
| Sandėlio grupė                           | Server, Storage & Netzwerk > Switche [+1398][-565] |
| Data transmission                        |                                                    |
| Firewall throughput                      | 0.35 Gbit/s                                        |
| VPN throughput                           | 0.09 Gbit/s                                        |
| Maximum firewall connections             | 20000                                              |
| Performance                              |                                                    |
| Built-in processor                       | No                                                 |
| Heat dissipation                         | 40.92 BTU/h                                        |
| Concurrent users                         | 15 user(s)                                         |
| Syslog                                   | Yes                                                |
| Mean time between failures (MTBF)        | 655130 h                                           |
| Network                                  |                                                    |
| Wi-Fi                                    | No                                                 |
| Concurrent SSL/VPN connections (maximum) | 15                                                 |
| VPN tunnels quantity                     | 10                                                 |
| Security                                 |                                                    |
| DDoS protection                          | Yes                                                |

|                                   |                                                        |
|-----------------------------------|--------------------------------------------------------|
| Firewall security                 | Y                                                      |
| <b>Protocols</b>                  |                                                        |
| Management protocols              | SNMP v1, v2c, v3                                       |
| <b>Management features</b>        |                                                        |
| LED indicators                    | Yes                                                    |
| Web-based management              | Yes                                                    |
| URL filtering                     | Yes                                                    |
| <b>Ports &amp; interfaces</b>     |                                                        |
| Ethernet LAN data rates           | 10,100,1000 Mbit/s                                     |
| WAN connection                    | Ethernet (RJ-45)                                       |
| DC-in jack                        | Yes                                                    |
| <b>Design</b>                     |                                                        |
| Built-in fan                      | No                                                     |
| <b>Power</b>                      |                                                        |
| Input current                     | 2 A                                                    |
| DC input voltage                  | 12 V                                                   |
| Power consumption (max)           | 12 W                                                   |
| <b>Certificates</b>               |                                                        |
| Certification                     | FCC Part 15 (Class B), IC, CE EMC (Class B), RCM, BSMI |
| <b>Operational conditions</b>     |                                                        |
| Operating temperature (T-T)       | 0 - 40 °C                                              |
| Storage temperature (T-T)         | -30 - 70 °C                                            |
| Operating relative humidity (H-H) | 10 - 90%                                               |
| Storage relative humidity (H-H)   | 10 - 90%                                               |
| <b>Weight &amp; dimensions</b>    |                                                        |
| Width                             | 216 mm                                                 |
| Depth                             | 143 mm                                                 |
| Height                            | 33 mm                                                  |
| Weight                            | 880 g                                                  |
| <b>Packaging data</b>             |                                                        |
| Package width                     | 276 mm                                                 |
| Package height                    | 185 mm                                                 |
| Package depth                     | 98 mm                                                  |
| Package weight                    | 1.41 kg                                                |

**Packaging content**

Cables included

LAN (RJ-45)