

LevelOne VDS-1202 network media converter 100 Mbit/s Grey

 Gamintojas: **LEVELONE** · Modelis: **VDS-1202** · EAN: **4015867209073** · Prekės kodas: **657927**


239,89 €

Kaina su PVM

 Be PVM: **198,26 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Trellis coding support up to 1024 discrete multi-tone bins and 4 Dip Switches for configuration settings
- ✓ Low-Latency for Video/Voice/Data applications
- ✓ Supports a VDSL connection of up to 2km over single pair copper wire
- ✓ Features selectable Fast and Interleaved modes
- ✓ Selectable fixed data rate and fixed SNR margin



Aprašymas

Why convert Ethernet to VDSL?

The LevelOne VDS-1202 converts your data from Ethernet to VDSL, making it easy to send high-bandwidth data over long distances. This new technology uses traditional twisted-pair telephone wiring instead of expensive Cat.5 cables.

New technology = cost-effective deployment

When using VDSL2 (Very High Speed Digital Subscriber Line) technology, users can transmit data up to 250 meters without having to add expensive Ethernet switches or cables to extend the network reach. And with 100Mbps downstream and 100Mbps upstream, VDSL2 technology provides ample space for all high bandwidth usage.

Fast transfer speeds? Yes.

Easy Installation? Yes.

VDS-1202 works especially well in applications where traditional copper phone lines are already installed: apartments, condominiums, hotels, university campus, etc. There is no need to run expensive Ethernet cables and installers can easily integrate VDSL technology into the existing network. The VDS-1202 is plug and play ready and requires minimum installation time.

Customized settings

Each VDS-1202 also allows for customized settings for advanced use. Using a built-in DIP switch, users can customize the behavior of the device to match the desired network configuration.

Annex B

For networks that utilize ISDN telephone systems.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Maximum data transfer rate	100 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3u
Ethernet LAN data rates	10,100 Mbit/s
Copper ethernet cabling technology	10BASE-T, 100BASE-T
Data transfer rate	100 Mbit/s
Auto MDI/MDI-X	Yes
Duplex system	Full, Half
Modulation	DMT
Performance	
Maximum transfer distance	1500 m
Features	
Internal	No
LED indicators	DSL, LAN, Power
Product colour	Grey
Housing material	Metal
Ports & interfaces	
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	2
RJ-11 ports quantity	2
DC-in jack	Yes
Power	

Input voltage	12 V
Input current	1 A
Weight & dimensions	
Width	90 mm
Depth	120 mm
Height	28 mm
Weight	330 g
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	5 - 95 °C
Packaging content	
AC adapter included	Yes
Quick installation guide	Yes
Packaging data	
Package width	150 mm
Package depth	235 mm
Package height	80 mm
Package weight	600 g
Package type	Box
Certificates	
Certification	CE, FCC, LVD, JATE
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990