

Vivolink VLSPSUB100 loudspeaker 2-way Wired 60 W

Gamintojas: **VIVOLINK** · Modelis: **VLSPSUB100** · EAN: **5715063260494** · Prekės kodas: **657973**



262,90 €

Kaina su PVM

Be PVM: **217,27 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Active powered Subwoofer 8" 50W
- ✓ 2x25W speaker output + line- out
- ✓ Silent on/off via automatic ECO mode after 90 seconds (less than 0,5 Watt)
- ✓ Audio inputs: 2xRCA + 100V + Balanced input + Bluetooth for (speaker out only)
- ✓ Switchable stereo / mono output



Aprašymas

Vivolink Active Subwoofer is a perfect match to all Vivolink speakers. It is designed to be mounted over ceiling or under furniture. Ideal for meeting rooms, hotels and auditoriums.

It have line input and loop out for active sattelite speakers.

Subwoofer can also be used together with passive sattelite speakers using the internal power amplifier for sattelinge speakers on 2 x 25W

- For rooms up to 200m2
- Power effect for subwoofer: 50 Watts
- Power effect for passive ceiling speakers:

(VLSPMTC60WT) 2x25Watts

- Inputs: 100V, Balanced in and RCA line in
- Bluetooth input for speaker out only (not supported for line-out)
- Outputs: RCA line out and Speaker out 2x 25W

- Line out for active speakers (VLSP60/65/61/70)
- Frequency range: 80Hz-20kHz
- Impedance: 8 Ohm

Techninė specifikacija

Specifications	
Sandėlio grupė	Entertainment Electronics > Lautsprecher/Audiosysteme [+294][-205] Entertainment Electronics > Speaker/Audio Systems [+1148][-646]
Loudspeakers	
Speaker type	2-way
Audio output channels	2.0 channels
Speaker placement	Wall-mountable
Number of drivers	2
Tweeter diameter (imperial)	2.54 cm (1")
Woofer diameter (imperial)	13.3 cm (5.25")
Audio	
RMS rated power	60 W
Peak Music Power Output (PMPO)	300 W
Speakers RMS power	30 W
Frequency range	45 - 20000 Hz
Impedance	4 Ω
Sensitivity	88 dB
Performance	
Recommended usage	Universal
Number of speakers	2
Housing material	Plastic
Volume control	Rotary
Certification	CE
Ports & interfaces	
Connectivity technology	Wired
6.35 mm (1/4-inch) input	1
Audio RCA inputs	1
Connector(s)	RCA, Minijack, Phoenix
Power	
Power source type	AC

AC input voltage	230 - 240 V
Power consumption (typical)	75 W
Power consumption (standby)	0.5 W
Current	1 A
Weight & dimensions	
Width	178 mm
Depth	162 mm
Height	240 mm
Weight	6.26 kg
Cord length	10 m
Packaging data	
Package width	440 mm
Package depth	210 mm
Package height	265 mm
Package weight	6.75 kg
Packaging content	
Cables included	AC
Other features	
Speaker weight	6.36 g
Front speaker frequency range	45 - 20000 Hz
Front speaker impedance	4 Ω
Front speaker sensitivity	88 dB
Housing colour	White
Power source	AC