

ATEN 4X4 True 4K HDMI Martrix Switch

Gamintojas: **ATEN** · Modelis: **VM0404HB-AT-G** · EAN: **4719264646829** · Prekės kodas: **657975**



571,89 €

Kaina su PVM

Be PVM: **472,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects any of 4 HDMI sources to any of 4 HDMI displays
- ✓ Supports True 4K resolutions up to 4096 x 2160 @ 60Hz (4:4:4)
- ✓ Multiple Control Methods – system management via front-panel pushbuttons, IR remote, RS-232 control, and Web GUI/Telnet via Ethernet connections
- ✓ HDMI (3D, Deep Color, 4K) and HDCP 2.2 compatible



Aprašymas

ATEN's VM0404HB is a True 4K HDMI Matrix Switch series that offers an easy and affordable way to route any of 4 HDMI video sources to any of 4 HDMI displays. Featured with the superior video resolutions up to 4096 x 2160 @ 60Hz (4:4:4), the VM0404HB delivers robust signal routing and ultra-fast digital video switching, making it perfect for applications where routing of True 4K digital signals is required, such as event venues, digital classrooms, auditoriums, department stores, and more.

1x VM0404HB 4 x 4 True 4K HDMI Matrix Switch

1x LIN2-418K-E12G Power Cord

1x 2XRT-0106G IR Remote Control

1x 2XRT-0003G IR Receiver

1x Rack Mounting Kit

1x User Instructions

Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Netzwerk > Switche [+1398][-565]

Features

Product type AV matrix switcher

Data transfer rate 18 Gbit/s

Maximum pixel clock 600 MHz

Maximum resolution 4096 x 2160 pixels

HDCP Yes

HDCP version 2.2

3D Yes

EDID management Yes

Design

Housing colour Black

Housing material Metal

Rack capacity 1U

Remote control included Yes

Display

Built-in display Yes

Ports & interfaces

HDMI input ports quantity 4

HDMI output ports quantity 4

RJ-45 input ports 1

RS-232 ports 1

Power

Power consumption (max) 17.8 W

AC input voltage 100 - 240 V

AC input frequency 50 - 60 Hz

Input current 1 A

Operational conditions

Operating temperature (T-T) 0 - 40 °C

Storage temperature (T-T) -20 - 60 °C

Operating relative humidity (H-H) 0 - 80%

Logistics data

Products per master (outer) case	1 pc(s)
Master (outer) case gross weight	3.76 kg
Master (outer) case length	556 mm
Master (outer) case width	247 mm
Master (outer) case height	153 mm
Master (outer) case net weight	2.75 kg
Harmonized System (HS) code	85299097

Weight & dimensions

Width	152.8 mm
Depth	437.2 mm
Height	44 mm
Weight	2.75 kg
Package width	247 mm
Package depth	556 mm
Package height	153 mm
Package weight	3.76 kg

Packaging content

Cables included	AC
Mounting brackets included	Yes