

# ATEN 8X8 True 4K HDMI Martrix Switch

Gamintojas: **ATEN** · Modelis: **VM0808HB-AT-G** · EAN: **4719264646836** · Prekės kodas: **657976**



## 1 250,90 €

Kaina su PVM

Be PVM: **1 033,80 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Connects any of 8 HDMI sources to any of 8 HDMI displays
- ✓ Supports True 4K resolutions up to 4096 x 2160 @ 60Hz (4:4:4)
- ✓ Supports HDR10+
- ✓ Multiple Control Methods – system management via front-panel pushbuttons, IR remote, RS-232 control, and Web GUI/Telnet via Ethernet connections
- ✓ View and control via ATEN Video Matrix Control App in a swift and agile way
- ✓ EDID Expert – selects optimum EDID settings for smooth power-up, high-quality display and use of the best video resolution across different screens
- ✓ Signaling rates up to 6 Gbits for flawless true 4K output
- ✓ Supports Dolby True HD and DTS HD Master audio
- ✓ HDMI (3D, Deep Color, 4K) and HDCP 2.2 compatible
- ✓ Supports Consumer Electronics Control (CEC)



## Aprašymas

ATEN's VM0808HB is a True 4K HDMI Matrix Switch series that offers an easy and affordable way to route any of 8 HDMI video sources to any of 8 HDMI displays. Featured with the superior video resolutions up to 4096 x 2160 @ 60Hz (4:4:4), the VM0808HB delivers robust signal routing and ultra-fast digital video switching, making it perfect for applications where routing of True 4K digital signals is required, such as event venues, digital classrooms, auditoriums, department stores, and more.

1x VM0808HB 8 x 8 True 4K HDMI Matrix Switch

1x LIN2-418K-E12G Power Cord

1x 2XRT-0106G IR Remote Control

- 1x 2XRT-0003G IR Receiver
- 1x Rack Mounting Kit
- 1x User Instructions

Techninė specifikacija

| Specifications                              |                                                    |
|---------------------------------------------|----------------------------------------------------|
| Sandėlio grupė                              | Server, Storage & Netzwerk > Switche [+1398][-565] |
| Features                                    |                                                    |
| Product type                                | AV matrix switcher                                 |
| Data transfer rate                          | 18 Gbit/s                                          |
| Maximum pixel clock                         | 600 MHz                                            |
| Maximum resolution                          | 4096 x 2160 pixels                                 |
| HDCP                                        | Yes                                                |
| HDCP version                                | 2.2                                                |
| 3D                                          | Yes                                                |
| High Dynamic Range (HDR) supported          | Yes                                                |
| Extended display identification data (EDID) | Yes                                                |
| Supported resolutions                       | 4096 x 2160, 3840 x 2160, 1920 x 1200              |
| Design                                      |                                                    |
| Housing colour                              | Black                                              |
| Housing material                            | Metal                                              |
| Rack mounting                               | Yes                                                |
| Rack capacity                               | 1U                                                 |
| Control type                                | Buttons                                            |
| On/off switch                               | Yes                                                |
| LED indicators                              | Yes                                                |
| Remote control included                     | Yes                                                |
| Display                                     |                                                    |
| Built-in display                            | Yes                                                |
| Ports & interfaces                          |                                                    |
| HDMI input ports quantity                   | 8                                                  |
| HDMI output ports quantity                  | 8                                                  |
| Ethernet LAN (RJ-45) ports                  | 1                                                  |
| RS-232 ports                                | 1                                                  |
| Remote (IR) input                           | 1                                                  |

**Power**

|                             |           |
|-----------------------------|-----------|
| Power consumption (max)     | 38.1 W    |
| Power consumption (typical) | 37.8 W    |
| AC input voltage            | 100-240 V |
| AC input frequency          | 50-60 Hz  |
| Input current               | 1 A       |

**Operational conditions**

|                                   |             |
|-----------------------------------|-------------|
| Operating temperature (T-T)       | 0 - 40 °C   |
| Storage temperature (T-T)         | -20 - 60 °C |
| Operating relative humidity (H-H) | 0 - 80%     |
| Storage relative humidity (H-H)   | 0 - 80%     |
| Heat dissipation                  | 177 BTU/h   |
| Heat dissipation (max)            | 179 BTU/h   |

**Logistics data**

|                                  |          |
|----------------------------------|----------|
| Products per master (outer) case | 1 pc(s)  |
| Master (outer) case gross weight | 5.63 kg  |
| Master (outer) case length       | 515 mm   |
| Master (outer) case width        | 338 mm   |
| Master (outer) case height       | 155 mm   |
| Master (outer) case net weight   | 4.15 kg  |
| Harmonized System (HS) code      | 85299097 |

**Weight & dimensions**

|                |          |
|----------------|----------|
| Width          | 432.4 mm |
| Depth          | 262.3 mm |
| Height         | 44 mm    |
| Weight         | 4.15 kg  |
| Package width  | 338 mm   |
| Package depth  | 515 mm   |
| Package height | 155 mm   |
| Package weight | 5.63 kg  |

**Packaging content**

|                   |     |
|-------------------|-----|
| Cables included   | AC  |
| Rack mount kit    | Yes |
| Quick start guide | Yes |

IR receiver included

Yes