

QNAP QNA-UC10G2T network card Ethernet 10000 Mbit/s

Gamintojas: **QNAP** · Modelis: **QNA-UC10G2T** · EAN: **4711103086575** · Prekės kodas: **658856**



542,90 €

Kaina su PVM

Be PVM: **448,68 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ USB Type-C Ethernet
- ✓ 10000 Mbit/s 10GBase-T
- ✓ Component for: PC



Aprašymas

Enjoy stable 10GbE high-speed networking using a USB Type-C connection to greatly enhance work efficiency, even on computers without built-in network ports.

Dual 10GbE Ports

Expand a single Type-C port into two 10GbE ports, delivering exceptional stability and flexible network configurations.

Broad interface compatibility

The QNA-UC10G2T includes a 1-meter USB 4 cable for connecting to your computer's USB 4 or Thunderbolt™ 3/4 ports.

Multi-system compatibility

Supports Windows®, macOS®, and Linux® computers (driver installation required).

Multi-speed support

Compatible with various network environments through Multi-Gigabit support for 10/5/2.5/1 GbE.

No Fan, No Noise

Fanless design ensures stable performance with reduced noise and maintenance, offering a quiet, reliable experience for long-term use.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Connectivity technology	Wired
Host interface	USB Type-C
Interface	Ethernet
Ethernet LAN (RJ-45) ports	2
USB ports quantity	1
Network	
Maximum data transfer rate	10000 Mbit/s
Ethernet LAN	Yes
Ethernet LAN data rates	100,1000,2500,5000,10000 Mbit/s
Cabling technology	10GBase-T
LAN controller	Marvell AQC113
Design	
Internal	No
Component for	PC
Product colour	Black, Silver
Compatible products	NAS : TBS-h574TX, TVS-h874T, TVS-h674T, TVS-472XT, TVS-672XT, TVS-872XT, TVS-h1288X w/ TBT3 AIC, TVS-h1688X w TBT3 AIC; Windows : USB4/TBT4; Mac : TBT3/TBT4;
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Packaging content	
Cables included	USB
Manual	Yes