

InLine 17991B cable gender changer HDMI A Micro HDMI D Black, Grey

Gamintojas: **INLINE** · Modelis: **17991B** · EAN: **4043718338191** · Prekės kodas: **659541**



16,90 €

Kaina su PVM

Be PVM: **13,97 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ HDMI A Straight Female
- ✓ Micro HDMI D Straight Male
- ✓ Connector contacts plating: Gold
- ✓ Housing material: Aluminium
- ✓ Black, Grey



Aprašymas

Reliable signal transmission:The 1:1 pin assignment enables direct transmission of audio and video signals without conversion.

Suitable for high-resolution applications:Supports UHD 8K and has been successfully tested in practice with 3840x2160 at 120 Hz and 4:4:4 8 bits.

Durable contact technology:Gold-plated contacts ensure stable transitions and reduce electrical resistance.

Robust construction:The aluminum housing protects the internal components and is suitable for demanding installations.

Flexible integration:Ideal for connecting or extending HDMI connections between micro HDMI sources and standard HDMI infrastructures.

The HDMI adapter reliably connects devices with micro HDMI outputs to existing HDMI infrastructure. The HDMI A socket on one side and the micro HDMI D plug on the other enable direct signal transmission without the need for additional active components. The 1:1 pin assignment ensures unadulterated transmission of digital audio and video signals.

The adapter supports resolutions up to UHD 8K and has been successfully tested with 3840x2160 at 120 Hz and 4:4:4 8 bits. This makes it suitable

for installations that require high image quality and stable signal paths. The gold-plated contacts reduce contact resistance and contribute to a permanently reliable connection.

The robust aluminum housing protects the contact surfaces and ensures high mechanical stability. The adapter can be flexibly integrated into both stationary and mobile AV setups. The recommended total length of the signal path is up to 1.5 meters and can reach a maximum of 2 meters.

With its compact design, the adapter offers a reliable solution for various professional applications in which micro HDMI signals need to be integrated into existing HDMI environments.

- Audio: Yes
- Housing material: Aluminum
- Side A: HDMI A socket
- Side B: Micro HDMI D plug
- Signal type: Audio/video
- Type: Gold-plated contacts
- Contact resistance: 3 ohms
- Insulation resistance: DC 300V 10M ohms
- Operating temperature: -10 °C to +60 °C
- Storage temperature: -20 °C to +80 °C
- Recommended total length: up to 1.5 m, maximum 2 m
- Dimensions: 19.3 mm x 12 mm x 10 mm
- Outer jacket: PVC black

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Connector 1	HDMI A
Connector 2	Micro HDMI D
Connector 1 gender	Female
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Performance	
Product colour	Black, Grey
Housing material	Aluminium
Maximum resolution (HDMI)	7680 x 4320 pixels
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 80 °C
Certificates	

Compliance certificates	RoHS, TÜV mark
-------------------------	----------------

Weight & dimensions

Width	20 mm
Depth	35 mm
Height	10 mm
Weight	7 g

Packaging data

Package width	140 mm
Package depth	70 mm
Package height	10 mm
Package weight	10 g
Package type	Polybag

Other features

Dimensions (WxDxH)	20 x 35 x 10 mm
--------------------	-----------------

Logistics data

Country of origin	Taiwan
-------------------	--------