

InLine 44432C PoE adapter 10 Gigabit Ethernet 52 V

Gamintojas: **INLINE** · Modelis: **44432C** · EAN: **4043718344178** · Prekės kodas: **659559**



84,91 €

Kaina su PVM

Be PVM: **70,17 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10,100,1000 Mbit/s Cat6
- ✓ Black
- ✓ Power over Ethernet (PoE) IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3an, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u



Aprašymas

Compatible with current PoE standards: Supports IEEE 802.3af/at/bt for flexible deployment in professional networks.

Powerful PoE++ port: Delivers up to 90 W via a Cat.6 or better cable – ideal for energy-intensive end devices.

Future-proof with 10GBase-T: The 10 Gigabit connection ensures maximum bandwidth even for demanding applications.

High operational reliability: Integrated surge and ESD protection reliably protects connected devices during continuous operation.

Network upgrade without switch replacement: Enables retrofitting of PoE++ functionality without interfering with existing switching infrastructure.

The InLine® PoE++ Injector 10Gigabit is the professional solution for expanding existing networks with powerful Power over Ethernet technology. It supports all relevant standards – IEEE 802.3af (PoE), 802.3at (PoE+) and 802.3bt (PoE++) – and thus offers full flexibility for the integration of modern network devices.

With a maximum output power of up to 90 W via a Cat.6 or better Ethernet cable, the injector reliably supplies even particularly power-hungry end devices. Typical applications include professional WLAN access points, IP cameras with PTZ function, video door intercom systems and thin clients. The integrated 10GBase-T port ensures that even large amounts of data are transferred without bottlenecks – a clear advantage in modern IT

environments.

Thanks to its simple plug-and-play installation, the PoE++ injector can be easily integrated into existing network infrastructures without having to replace the existing switch architecture. The integrated surge and ESD protection ensures reliable operation even under demanding conditions.

Standards: IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3an 10GBase-T, IEEE 802.3af PoE, IEEE 802.3at PoE+, IEEE 802.3bt PoE

Port 'Data in': 1x 10GBase-T RJ45

Port 'PoE out': 1x 10GBase-T RJ45

Power supply: AC 100 V - 240 V 50/60 Hz / DC 52 V / 1.92 A

PoE output voltage: DC 44-57 V

PoE output power: max. 90 watts

Overvoltage protection: Connection overvoltage: differential mode 2KV, common mode 6KV / Electrostatic: ESD 6KV, air 8KV (Class B)

LED indicators: POWER

Dimensions (L x W x H): 187 x 95 x 40 mm

Weight: approx. 490 g

Ambient conditions: Operating temperature -20-50 °C, storage temperature -40-85 °C, humidity 5-90 % non-condensing

Scope of delivery: 1x InLine® PoE++ injector 10 Gigabit, 802.3bt, 90 Watt, 2x operating instructions (German/English), 1x power cable

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Network	
Ethernet interface type	10 Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+, PoE++ (4PPoE)
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3an, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u
Cable types supported	Cat6
Features	
Product colour	Black
LED indicators	Power
Power protection features	Over voltage, Surge protection
Ports & interfaces	
RJ-45 input ports	1
RJ-45 output ports	1
Power	
Power over Ethernet (PoE) voltage	52 V
Output power	90 W

AC adapter input voltage	100 - 240 V
AC adapter frequency	50/60 Hz
Input current	1.92 A
Certificates	
Compliance certificates	CE, TÜV mark
Weight & dimensions	
Width	90 mm
Depth	190 mm
Height	43 mm
Weight	488 g
Dimensions (WxDxH)	90 x 190 x 43 mm
Packaging content	
Power cord included	Yes
Manual	Yes
Packaging data	
Package width	190 mm
Package depth	255 mm
Package height	60 mm
Package weight	752 g
Package volume	0 cm³
Package type	Box
Logistics data	
Country of origin	Taiwan