

InLine Gigabit Ethernet PCI Adapter 1x RJ45

Gamintojas: **INLINE** · Modelis: **51115B** · EAN: **4043718333257** · Prekės kodas: **659560**



27,90 €

Kaina su PVM

Be PVM: **23,06 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCI
- ✓ Output interface: RJ-45
- ✓ 1 Gbit/s



Aprašymas

Powerful 10/100/1000BASE-T network card with Realtek RTL8169SC chipset
Supports 1 Gb/s data transfer rate over existing CAT.5e or higher copper cabling
Compatible with PCI V2.2 (32/64-bit, 33/66 MHz) slots
Supports Wake on LAN, VLAN tagging and ACPI power management
Broad driver support for Windows, Linux and macOS

The InLine® Gigabit PCI network card offers a powerful and cost-effective solution for connecting to wired networks in the home and office. With a maximum data rate of 1 Gb/s, it is ideal for fast file transfers, media streaming or reliable Internet connections. Thanks to its Realtek RTL8169SC chipset, the card guarantees high compatibility and stability. It can be easily integrated into systems with PCI V2.2 slots (32/64-bit, 33/66 MHz). The network card supports modern network functions such as full-duplex flow control, IEEE 802.1Q VLAN tagging and Wake on LAN (WoL). Crossover detection and auto-correction mode are also part of the range of functions. With support for current operating systems such as Windows, Linux and macOS, the network card is versatile. An optional boot ROM is also supported, making it suitable for special network requirements.

Technical specifications:

Chip set: Realtek RTL8169SC

Interface: PCI V2.2 (32/64-bit, 33/66 MHz)

Transmission rate: 10 / 100 / 1000 Mb/s

Compatible cabling: CAT.5e or higher

Network standards: IEEE 802.3, 802.3u, 802.3ab

Supports: Full-duplex flow control, VLAN tagging, Wake on LAN (WoL), ACPI, Boot ROM (optional)

Crossover detection and auto-correction

Compatible operating systems: Windows 98SE or newer, Server 2003 or newer, Linux kernel ≥ 2.4 , macOS X 10.4 or newer

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Network > Network Adapters [+1948][-605]

Ports & interfaces

Host interface	PCI
Output interface	RJ-45
Host interface gender	Male
Expansion card standard	PCI 2.2

Design

Internal	Yes
LED indicators	Yes
Country of origin	Taiwan

Features

Data transfer rate (max)	1 Gbit/s
--------------------------	----------

System requirements

Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows 98SE, Windows Vista, Windows XP
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2
Server operating systems supported	Windows Server 2003, Windows Server 2007, Windows Server 2008, Windows Server 2012, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022

Weight & dimensions	
Width	130 mm
Depth	1.22 mm
Height	120 mm
Weight	2 kg
Packaging data	
Package width	140 mm
Package depth	150 mm
Package height	30 mm
Package weight	48 g
Other features	
Dimensions (WxDxH)	130 x 1.22 x 120 mm