

InLine 10 Gigabit network card, 1x SFP+, PCIe x8, incl. low profile bracket

Gamintojas: **INLINE** · Modelis: **51130A** · EAN: **4043718333295** · Prekės kodas: **659566**



61,90 €

Kaina su PVM

Be PVM: **51,16 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: PCIe
- ✓ Output interface: SFP+
- ✓ 10 Gbit/s



Aprašymas

10 Gb/s high-performance network card for SFP+ fiber optic modules
Intel JL82599EN chipset for stable and professional performance
PCIe x8 interface according to PCIe v2.0 standard
Supports VLAN, jumbo frames, RSS and full-duplex flow control
Compatible with Windows, server and Linux systems

The InLine® 10 Gigabit network card with SFP+ port is the perfect choice for companies that want to implement high bandwidths via fiber optics. Equipped with the Intel JL82599EN chipset, it provides a stable and efficient connection for demanding applications in the data center or in professional IT environments.

The card uses a PCIe x8 interface in accordance with PCI Express Revision 2.0 and supports a variety of modern functions such as IEEE 802.1Q VLAN tagging, full-duplex flow control, receive side scaling (RSS) as well as checksum swapping and device queuing for virtual machines. Jumbo frames up to 16KB are also supported.

Compatibility with common protocols such as IPv4 and IPv6 as well as support for current operating systems makes the card extremely versatile. It is suitable for fiber optic connections with 10GBASE-SR, -LR, -ER and much more.

Technical specifications:

Chip set: Intel JL82599EN

Interface: PCI Express x8, Revision 2.0

Port: 1x SFP+ (for 10GbE fiber optic modules)

Supported standards: IEEE 802.3ae, 802.3x, 802.1Q

Supported: 10GBASE-SR, -LR, -ER, -SW, -LW, -EW

Network protocols: IPv4, IPv6

Functions: RSS, VLAN tagging, jumbo frames (up to 16KB), checksum swapping, VM queue support

Compatible operating systems: Windows 7 or newer, Server 2008 or newer, Linux kernel ≥ 2.6

Scope of delivery: Network card incl. low-profile slot bracket

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	SFP+
Expansion card standard	PCIe 2.0
Design	
Internal	Yes
Cooling type	Passive
Country of origin	China
Features	
Data transfer rate (max)	10 Gbit/s
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2
Server operating systems supported	Windows Server 2008, Windows Server 2012, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022
Weight & dimensions	
Width	150 mm

Depth	1.89 mm
Height	120 mm
Weight	2 kg
Packaging data	
Mounting brackets included	Yes
Package width	175 mm
Package depth	150 mm
Package height	30 mm
Package weight	99 g
Other features	
Dimensions (WxDxH)	150 x 1.89 x 120 mm