

InLine Dual 10 Gigabit network card, 2x SFP+, PCIe x8, incl. LP bracket

Gamintojas: **INLINE** · Modelis: **51131A** · EAN: **4043718333301** · Prekės kodas: **659567**



138,90 €

Kaina su PVM

Be PVM: **114,79 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Two SFP+ ports for 10GbE via fiber optic flexible through module selection
- ✓ Supports VLAN, jumbo frames, RSS and virtual machines
- ✓ Intel JL82599EN chipset for stable performance in continuous operation
- ✓ Compatible with Windows and Linux
- ✓ PCIe x8 interface according to revision 2.0 for professional applications



Aprašymas

Two SFP+ ports for 10GbE via fiber optic flexible through module selection
 Intel JL82599EN chipset for stable performance in continuous operation
 PCIe x8 interface according to revision 2.0 for professional applications
 Supports VLAN, jumbo frames, RSS and virtual machines
 Compatible with Windows and Linux

The InLine® Dual 10 Gigabit network card with two SFP+ ports offers the highest performance for fiber-based network connections. Equipped with the Intel JL82599EN chipset, it enables reliable data transmission at up to 10 Gb/s per port - ideal for servers, data centers and virtualized

infrastructures.

The card supports common standards such as 10GBASE-SR, -LR, -ER and many more. (IEEE 802.3ae) and offers functions such as VLAN tagging, full duplex flow control, receive side scaling (RSS), jumbo frames up to 16KB and support for virtual machines (VM queues). Interrupt throttling also improves CPU utilization.

Thanks to the PCIe x8 interface (Rev. 2.0), the card can be flexibly integrated. It is supplied with a low-profile slot bracket – also ideal for compact systems.

Technical specifications:

- Chipset: Intel JL82599EN
- Interface: PCIe x8, Revision 2.0
- Ports: 2x SFP+ (10GbE fiber optic)
- Supported standards: IEEE 802.3ae, 802.3x, 802.1Q
- Supports: 10GBASE-SR/LR/ER/SW/LW/EW
- Network protocols: IPv4, IPv6
- Functions: VLAN, RSS, jumbo frames (up to 16KB), checksum offload, VM queue support
- Compatible operating systems: Windows 7 or newer, Server 2008 or newer, Linux Kernel ≥ 2.6
- Operating temperature: 0° C – 55° C
- Storage temperature: -40° C – 70° C
- Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	PCIe
Output interface	SFP+
Host interface gender	Male
Expansion card standard	PCIe 2.0
Design	
Internal	Yes
Cooling type	Passive
Country of origin	China
Features	
Data transfer rate (max)	10 Gbit/s
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2

Server operating systems supported	Windows Server 2008, Windows Server 2012, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022
------------------------------------	--

Weight & dimensions

Width	150 mm
Depth	1.9 mm
Height	120 mm
Weight	2 kg

Packaging data

Mounting brackets included	Yes
Package width	175 mm
Package depth	150 mm
Package height	30 mm
Package weight	101 g

Other features

Dimensions (WxDxH)	150 x 1.9 x 120 mm
--------------------	--------------------