

InLine 57885E KVM switch Rack mounting Black

Gamintojas: **INLINE** · Modelis: **57885E** · EAN: **4043718344284** · Prekės kodas: **659571**



141,90 €

Kaina su PVM

Be PVM: **117,27 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Rack mounting Black
- ✓ Number of computers controlled: 2
- ✓ Video port type: HDMI/USB
- ✓ 4K Ultra HD 3840 x 2160 pixels
- ✓ Housing material: Metal
- ✓ DC 12 W External power adapter



Aprašymas

Two devices - one workspace: Switch easily between an HDMI and a USB-C device with just one display, keyboard and mouse.

Excellent image quality: Supports 4K@60Hz with 4:4:4 colour sampling and Dolby Vision – crystal-clear images for professional demands.

Flexible control: Switch via hotkey, IR remote control, front button or RS-232 – ideal for individual setups or automation.

Universal compatibility: Works with Windows, macOS and Linux – no driver installation required.

Additional functionality: USB-C devices can be charged simultaneously and USB peripherals can be used at up to 5 Gb/s.

The InLine® KVM switch with 2-way switching via HDMI and USB-C offers a convenient way to operate two computers with just one monitor, one keyboard and one mouse. Video output is in brilliant 4K resolution at 60 Hz with full support for modern HDR formats such as Dolby Vision or HDR10+.

Thanks to four USB 3.2 Gen.1 ports, a mouse, keyboard and other peripherals such as external drives or webcams can be used centrally. Particularly practical: the integrated charging function with USB-C Power Delivery (PD 3.0) allows a connected end device to be powered simultaneously.

Switching is flexible via front button, IR remote control, hotkeys or RS-232 interface – also ideal for professional IT setups or automated applications.

The switch is completely driver-free and can be used immediately with Windows, macOS or Linux.

The robust metal housing, comprehensive signal support and ESD protection round off the professional appearance.

The InLine® KVM switch is therefore the ideal solution for home offices, training courses, system integration and demanding workstation environments.

HDMI input: 1 × HDMI (type A, 19-pin)

USB-C input: 1 × USB-C (AV signal), 1 × USB-C (charging function, PD 3.0)

HDMI output: 1 × HDMI (type A, 19-pin)

USB ports: 4 × USB 3.2 Gen.1 (USB-A), 1 × USB host (USB-B)

RS-232: 3-pin terminal connection

IR EXT: 3.5 mm stereo jack (38 kHz)

Audio output: 3.5 mm stereo jack (PCM 2.0CH)

Resolution: up to 4K@60Hz, 2K@144Hz

Colour depth: 8 / 10 / 12 bits

Colour spaces: RGB 4:4:4, YCbCr 4:4:4, 4:2:2, 4:2:0

HDR support: HDR, HDR10, HDR10+, Dolby Vision, HLG

HDMI version: HDMI 2.0

DP compatibility: DP 1.4 (for USB-C input)

HDCP compatibility: HDCP 2.3

Supported audio formats HDMI IN/OUT: LPCM, Dolby Digital/Plus/EX, Dolby TrueHD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DTS:X, DSD

Latency: no video or audio delay

CEC support: yes

ESD protection: ±8 kV air / ±4 kV contact

Housing: metal, black

Dimensions: 175 × 100 × 30 mm

Weight: 505 g

Operating temperature: 0–40 °C

Storage temperature: –20–60 °C

Humidity: 20–90% (non-condensing)

Recommended cable lengths

HDMI: up to 5 m (4K@60Hz), up to 10 m (1080p)

USB-C: up to 1.5 m

Note: Use of 'Premium High Speed HDMI' or 'USB-C' cables recommended

External power supply (power adapter)

Type: External plug-in power adapter with lock

Input voltage: 100–240 V AC, 50/60 Hz

Output voltage: 12.0 V DC

Output current: max. 1.0 A

Output power: 12.0 W

Average operating efficiency: 85.23%

Efficiency at low load (10%): 78.53%

Power consumption at zero load: 0.09 W

Scope of delivery

1 × InLine® KVM switch, 2-port, HDMI, USB-C, 4K60Hz

- 1 × IR remote control
- 1 × IR receiver cable (1.5 m, 38 kHz)
- 1 × HDMI cable (1.5 m)
- 1 × USB cable (USB 3.2 Gen.1, USB-A to USB-B, 1.8 m)
- 1 × USB-C cable (USB 3.2 Gen.2, male on both sides, 1 m)
- 1 × 12 V/1 A power supply with lock
- 1 × 3-pin terminal connection plug
- 2 × mounting brackets
- 4 × screws (KM3×4)
- 1 × user manual in German/English

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Netzwerk > Switches [+1398][-565]
Ports & interfaces	
Number of computers controlled	2
Video port type	HDMI/USB
HDMI ports quantity	2
HDMI version	2.1
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	4
USB connector type	USB Type-A, USB Type-B, USB Type-C
Serial port type	RS-232
Serial ports quantity	1
Audio connections	Yes
DC-in jack	Yes
Performance	
HD type	4K Ultra HD
Maximum resolution	3840 x 2160 pixels
Data transfer rate (max)	5 Gbit/s
High Dynamic Range (HDR) supported	Yes
HDCP	Yes
Maximum refresh rate	144 Hz
HDCP version	2.3
Audio decoding technologies	DTS-HD, DTS-HD Master Audio, DTS:X, Dolby Atmos, Dolby Digital, Dolby Digital EX, Dolby Digital Plus, Dolby TrueHD
Consumer Electronics Control (CEC) support	Yes

Design

Rack mounting	Yes
Product colour	Black
Housing material	Metal
LED indicators	Yes

Display

Built-in display	No
------------------	----

Power

Power source	DC
Input voltage	100 - 240 V
AC input frequency	50/60 Hz
Output voltage	12 V
Output current	1 A
Power consumption (typical)	12 W
External power adapter	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3

Sustainability

Compliance certificates	TÜV mark
-------------------------	----------

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%

Weight & dimensions

Width	100 mm
Depth	175 mm
Height	30 mm
Weight	503 g

Packaging data

Package volume	14600 cm ³
Package type	Box

Packaging content

Cables included	HDMI, IR, USB Type-A to USB Type-B
Manual	Yes

AC adapter included	Yes
---------------------	-----

Rack mount kit	Yes
----------------	-----

Remote control included	Yes
-------------------------	-----

Other features

Dimensions (WxDxH)	100 x 175 x 30 mm
--------------------	-------------------

Colour depth	12 bit
--------------	--------

Logistics data

Country of origin	Taiwan
-------------------	--------