

InLine SATA 6Gb/s Controller with 4 SATA Ports PCI-Express 2.0

Gamintojas: **INLINE** · Modelis: **76617M** · EAN: **4043718333219** · Prekės kodas: **659581**



56,89 €

Kaina su PVM

Be PVM: **47,02 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Internal
- ✓ Host interface: SATA
- ✓ Output interface: SATA
- ✓ 6 Gbit/s



Aprašymas

Flexible storage expansion via PCIe: Provides four additional SATA 6Gb/s ports for internal storage solutions – ideal for workstations and servers.

High data rate thanks to SATA 6Gb/s: Supports fast SSDs and modern hard drives for maximum performance with minimal effort.

Broad compatibility thanks to PCIe x1 interface: Can be used in x1, x4, x8 and x16 slots – for maximum flexibility in different system architectures.

Hot plug & hot swap functionality: Drives can be added or removed during operation – ideal for maintenance environments.

Supports NCQ & port multipliers: Enables efficient data processing and complex storage structures in professional environments.

The InLine® interface card with four SATA 6Gb/s ports offers a powerful solution for storage expansion via PCIe. Equipped with the Marvell 88SE9215 chipset, it delivers stable performance with high data throughput – ideal for professional storage applications.

The card supports PCI Express 2.0 with a x1 interface, but is compatible with x1, x4, x8 and x16 slots, allowing it to be installed in almost any modern PC or server. Thanks to backward compatibility with SATA 3Gb/s and 1.5Gb/s, older drives can also be used without any problems.

With support for hot plug and hot swap, the card is ideal for IT maintenance scenarios and flexible expansion during operation. Native Command Queuing (NCQ) and port multipliers (FIS or command-based) are fully supported, so even complex storage concepts are no problem.

The InLine® PCIe SATA card is suitable for use in workstations, small servers or NAS solutions where performance, flexibility and operational

reliability are crucial.

Chipset: Marvell 88SE9215

Interface: PCI Express 2.0 x1 (compatible with x1, x4, x8, x16)

Connections: 4x SATA 6Gb/s

Compatible with SATA 6Gb/s, 3Gb/s, 1.5Gb/s

Supports hot plug & hot swap

Supports NCQ (Native Command Queuing)

Supports port multipliers with FIS or command-based switching

Operating systems: Windows XP/Server 2003 or newer, Linux from kernel 2.6.x

Operating temperature: 0° C – 55° C

Storage temperature: -40° C – 70° C

Humidity: 10% - 90% non-condensing

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Network Adapters [+1948][-605]
Ports & interfaces	
Host interface	SATA
Output interface	SATA
Host interface gender	Male
Expansion card standard	PCIe 2.0
SATA revision	3
Design	
Internal	Yes
Hot-swap	Yes
Hot-Plug support	Yes
Features	
Data transfer rate (max)	6 Gbit/s
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP
Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2
Server operating systems supported	Windows Server 2003, Windows Server 2007, Windows Server 2008, Windows Server 2012, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022
Weight & dimensions	
Width	120 mm

Depth	1.1 mm
Height	80 mm
Weight	2 kg
Packaging data	
Package width	140 mm
Package depth	150 mm
Package height	30 mm
Package weight	38 g
Other features	
Dimensions (WxDxH)	120 x 1.1 x 80 mm